

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

**LEATHER ADHESIVE 20ML FILLED TUBE** 

Supercedes Date: 19-Dec-2016

Revision Date 03-Sep-2018 Revision Number 1.01

# Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1. Product Identifier

Product Name LEATHER ADHESIVE 20ML FILLED TUBE

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Adhesives.
Uses advised against None known

## 1.3. Details of the supplier of the safety data sheet

### **Company Name**

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

## 1.4. Emergency telephone number

United Kingdom	+44 (1785) 272650
Ireland	+353 (1) 8624900 (Monday- Friday 9am-5pm)

### Section 2: HAZARDS IDENTIFICATION

#### 2.1. Classification of the substance or mixture

## Classification according to Regulation (EC) No. 1272/2008 [CLP]

Serious eye damage/eye irritation	Category 2 - (H319)
Skin sensitisation	Category 1 - (H317)
Specific target organ toxicity (single exposure)	Category 3 - (H336)
Chronic aquatic toxicity	Category 3 - (H412)
Flammable liquids	Category 2 - (H225)

#### 2.2. Label Elements

## Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Contains Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW, Methyl ethyl ketone, Acetone





Signal word DANGER

**LEATHER ADHESIVE 20ML FILLED TUBE** 

Supercedes Date: 19-Dec-2016

Revision Date 03-Sep-2018 Revision Number 1.01

#### **Hazard statements**

H412 - Harmful to aquatic life with long lasting effects

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

H317 - May cause an allergic skin reaction

H225 - Highly flammable liquid and vapour

## **EU Specific Hazard Statements**

EUH066 - Repeated exposure may cause skin dryness or cracking

EUH205 - Contains epoxy constituents. May produce an allergic reaction

#### **Precautionary statements**

P101 - If medical advice is needed, have product container or label at hand

P102 - Keep out of reach of children

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P271 - Use only outdoors or in a well-ventilated area

P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

P403 + P233 - Store in a well-ventilated place. Keep container tightly closed

P501 - Dispose of contents/ container to an approved waste disposal plant

#### **Additional information**

This product requires tactile warnings if supplied to the general public

#### 2.3. Other Hazards

#### **General Hazards**

In use may form flammable/explosive vapour-air mixture.

## PBT and vPvB assessment

The components in this formulation do not meet the criteria for classification as PBT or vPvB

## Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

## 3.1 Substances

Mixture

#### 3.2 Mixtures

Chemical Name	EC No.	CAS No.	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH Registration Number
Methyl ethyl ketone	201-159-0	78-93-3	>25 - <40	Eye Irrit. 2 (H319) (EUH066) STOT SE 3 (H336) Flam. Liq. 2 (H225)		01-2119457290-43 -XXXX
Acetone	200-662-2	67-64-1	>25 - <40	Eye Irrit. 2 (H319) (EUH066) STOT SE 3 (H336) Flam. Liq. 2 (H225)		01-2119471330-49 -XXXX
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	500-033-5	25068-38-6	1 - <5	Skin Irrit. 2 (H315) Eye Irrit. 2 (H319) Skin Sens. 1 (H317) Aquatic Chronic 2 (H411)	Eye Irrit. 2 :: C>=5% Skin Irrit. 2 :: C>=5%	01-2119456619-26 -xxxx

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classifed, however, the substance is listed in section 3 as it has an OEL.

#### **LEATHER ADHESIVE 20ML FILLED TUBE**

Supercedes Date: 19-Dec-2016

Revision Date 03-Sep-2018 Revision Number 1.01

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

## Section 4: FIRST AID MEASURES

#### 4.1. Description of first aid measures

General Advice If medical advice is needed, have product container or label at hand.

**Inhalation** Remove to fresh air.

**Skin Contact**Wash with plenty of soap and water. In the case of skin irritation or allergic reactions see

a doctor.

**Eye contact** Immediately flush with plenty of water. After initial flushing, remove any contact lenses

and continue flushing for at least 15 minutes. If eye irritation persists: Get medical

advice/attention.

**Ingestion** If swallowed, do not induce vomiting: seek medical advice immediately and show this

container or label.

Self-Protection of the First Aider Use personal protection recommended in Section 8. Isolate the hazard area and deny

entry to unnecessary and unprotected personnel.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Irritating to eyes. May cause allergic skin reaction. Drowsiness. Dizziness.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically.

## Section 5: FIREFIGHTING MEASURES

## 5.1. Extinguishing media

## **Suitable Extinguishing Media**

Use CO2, dry chemical, or foam. Move containers from fire area if you can do it without risk.

#### **Unsuitable Extinguishing Media**

Do not use a solid water stream as it may scatter and spread fire

## 5.2. Special hazards arising from the substance or mixture

Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

#### 5.3. Advice for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

## Section 6: ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

#### **Personal Precautions**

Remove all sources of ignition. Evacuate personnel to safe areas. Ensure adequate ventilation, especially in confined areas.

Water spray may reduce vapour; but may not prevent ignition in closed spaces.

### For emergency responders

Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected

**LEATHER ADHESIVE 20ML FILLED TUBE** 

Supercedes Date: 19-Dec-2016 Revision Number 1.01

personnel.

#### 6.2. Environmental precautions

Collect spillage. Keep out of drains, sewers, ditches and waterways.

#### 6.3. Methods and material for containment and cleaning up

**Methods for Containment** Prevent further leakage or spillage if safe to do so.

Methods for cleaning up

Dyke to collect large liquid spills. Soak up with inert absorbent material. Take up

mechanically, placing in appropriate containers for disposal. Use clean non-sparking

Revision Date 03-Sep-2018

tools to collect absorbed material.

6.4. Reference to other sections

Reference to other sections See Section 12: ECOLOGICAL INFORMATION

Section 7: HANDLING AND STORAGE

Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## Section 7: HANDLING AND STORAGE

## 7.1. Precautions for safe handling

#### Advice on safe handling

Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Take precautionary measures against static charges. Use explosion-proof electrical/ ventilating/ lighting/ equipment. Use personal protection recommended in Section 8.

#### **General Hygiene Considerations**

Do not eat, drink or smoke when using this product. Regular cleaning of equipment, work area and clothing is recommended.

## 7.2. Conditions for safe storage, including any incompatibilities

#### **Storage Conditions**

Keep only in the original container/package in a cool well-ventilated place. Keep out of reach of children.

#### 7.3. Specific end use(s)

#### Specific Use(s)

Adhesives.

## Other Information

Observe technical data sheet.

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

## 8.1. Control parameters

Chemical Name	European Union	Ireland	United Kingdom
Methyl ethyl ketone	TWA: 200 ppm	TWA: 200 ppm	TWA: 200 ppm
78-93-3	TWA: 600 mg/m <sup>3</sup>	TWA: 600 mg/m <sup>3</sup>	TWA: 600 mg/m <sup>3</sup>
	STEL: 300 ppm	STEL: 300 ppm	STEL: 300 ppm
	STEL: 900 mg/m <sup>3</sup>	STEL: 900 mg/m <sup>3</sup>	STEL: 899 mg/m <sup>3</sup>
		Sk*	Sk*
Acetone	TWA: 500 ppm	TWA: 500 ppm	TWA: 500 ppm
67-64-1	TWA: 1210 mg/m <sup>3</sup>	TWA: 1210 mg/m <sup>3</sup>	TWA: 1210 mg/m <sup>3</sup>
		STEL: 1500 ppm	STEL: 1500 ppm
		STEL: 3630 mg/m <sup>3</sup>	STEL: 3620 mg/m <sup>3</sup>
Talc	=	TWA: 10 mg/m <sup>3</sup>	TWA: 1 mg/m <sup>3</sup>
14807-96-6		TWA: 0.8 mg/m <sup>3</sup>	STEL: 3 mg/m <sup>3</sup>
		STEL: 30 mg/m <sup>3</sup>	
		STEL: 2.4 mg/m <sup>3</sup>	

Chemical Name European Union Ireland United Kingdom
---

**LEATHER ADHESIVE 20ML FILLED TUBE** 

Supercedes Date: 19-Dec-2016

Revision Date 03-Sep-2018 Revision Number 1.01

Methyl ethyl ketone	-	-	70
78-93-3			

Derived No Effect Level (DNEL) No information available

Predicted No Effect Concentration No information available.

(PNEC)

8.2. Exposure controls

**Engineering Controls** Ensure adequate ventilation, especially in confined areas.

**Personal Protective Equipment** 

**Respiratory Protection** 

**Eye/Face Protection** Tight sealing safety goggles. Face protection shield.

Hand Protection Wear protective gloves. The breakthrough time of the gloves depends on the material

and the thickness as well as the temperature.

Skin and Body Protection Wear appropriate personal protective clothing to prevent skin contact. Antistatic

footwear. Wear fire/flame resistant/retardant clothing. Gloves made of plastic or rubber. In case of mist, spray or aerosol exposure wear suitable personal respiratory protection

Remarks • Method

and protective suit. In case of inadequate ventilation wear respiratory protection.

**Recommended filter type:** Organic gases and vapours filter conforming to EN 14387.

No information available

No information available

No information available

No information available

Environmental Exposure Controls Do not allow into any sewer, on the ground or into any body of water.

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1. Information on basic physical and chemical properties

Physical StateLiquidAppearanceLiquidColourColourlessOdourCharacteristic

Odour Threshold No information available

Property Values

pH No information available

Melting point / freezing point

Boiling point / boiling range
Flash Point

Evaporation Rate

No information available

56.1 °C / 133 °F

-20 °C / -4 °F

No information available

Flammability (solid, gas) Flammability Limit in Air

Upper flammability or explosive

limits

Lower flammability or explosive

limits

**Vapour Pressure** 

No information available **Vapour Density Relative Density** No information available **Water Solubility** No information available Solubility in Other Solvents No information available **Partition coefficient** No information available No information available **Autoignition Temperature Decomposition Temperature** No information available No information available **Explosive Properties Oxidising Properties** No information available No information available **Kinematic Viscosity** 

Dynamic Viscosity No information available

9.2. Other information

Softening Point
Molecular Weight
No information available
No information available
No information available

#### **LEATHER ADHESIVE 20ML FILLED TUBE**

Supercedes Date: 19-Dec-2016

Revision Date 03-Sep-2018 Revision Number 1.01

Solid content (%)

Density

Bulk Density

VOC (volatile organic compound)

No information available
No data available
No information available

## Section 10: STABILITY AND REACTIVITY

#### 10.1. Reactivity

Stable under recommended storage conditions.

#### 10.2. Chemical stability

Stable under recommended storage conditions.

**Explosion Data** 

Sensitivity to Mechanical Impact None.

Sensitivity to Static Discharge May be ignited by friction, heat, sparks or flames.

#### 10.3. Possibility of hazardous reactions

#### **Possibility of Hazardous Reactions**

None under normal processing.

#### 10.4. Conditions to avoid

Keep away from heat, sparks and flames.

#### 10.5. Incompatible materials

Strong acids and bases.

## 10.6. Hazardous decomposition products

None under normal use conditions.

## Section 11: TOXICOLOGICAL INFORMATION

## 11.1. Information on toxicological effects

#### Information on likely routes of exposure

#### **Product Information**

No information or data specific to the product on this toxicological (health) effect is available.

InhalationNo data available.Eye contactSeverely irritating to eyes.Skin ContactNo data available.IngestionNo data available.

**Sensitisation** May cause sensitisation by skin contact.

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin Corrosion/Irritation Not applicable.

Serious eye damage/eye irritation Not applicable.

**Sensitisation** Not applicable.

Germ Cell Mutagenicity Not applicable.

**LEATHER ADHESIVE 20ML FILLED TUBE** 

Supercedes Date: 19-Dec-2016

Revision Date 03-Sep-2018 Revision Number 1.01

Caraina gamiaitu Not appliaabla

Carcinogenicity Not applicable.

**Reproductive Toxicity** No information available.

**STOT - single exposure** Based on available data, the classification criteria are not met.

**STOT - repeated exposure**Based on available data, the classification criteria are not met.

Target Organ Effects Central nervous system, Eyes, Respiratory system, Skin.

Aspiration hazard Based on available data, the classification criteria are not met.

Numerical measures of toxicity

**Acute Toxicity** 

The following values are calculated based on chapter 3.1 of the GHS document mg/kg mg/l

Component Information

**Toxicity Data** Data obtained on the component(s) include

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl ethyl ketone	= 2483 mg/kg (Rat)	= 5000 mg/kg ( Rabbit )	= 11700 ppm (Rat) 4 h
78-93-3			
Acetone	= 5800 mg/kg (Rat)	>15800 mg/Kg (rat)	= 79 mg/l( Rat ) 4 h
67-64-1			
Bisphenol-A-Epichlorhydrin Epoxy	LD50 (rat) > 2000 mg/kg OECD	>2000 mg/Kg (rat)	-
resin <= 700 MW	420		
25068-38-6			

## Section 12: ECOLOGICAL INFORMATION

## 12.1. Toxicity

**Ecotoxicity** Harmful to aquatic life with long lasting effects

## **Component Information**

Data obtained on the component(s) include

Chemical Name	Algae/aquatic plants	Fish	Crustacea	M-Factor
Methyl ethyl ketone	EC50=1972 mg/l	LC50: 3130 - 3320mg/L (96h,	EC50 48 h > 308 mg/L	
78-93-3	(Pseudokirchneriella	Pimephales promelas)	(Daphnia magna )	
	subcapitata)			
Acetone	-	LC50 96 h 4.74 - 6.33 mL/L	EC50 48 h 10294 - 17704	
67-64-1		(Oncorhynchus mykiss)	mg/L (Daphnia magna Static)	
Bisphenol-A-Epichlorhydrin	EC50 (72h) = 9.4 mg/L	1.2 mg/l 96Hr (Oncorhynchus	2.7 mg/l 48hr Daphia Magna	
Epoxy resin <= 700 MW	(Scenedesmus capricornutum)	mykiss)		
25068-38-6	EPA-660/3-75-009			

## 12.2. Persistence and degradability

No information available.

#### 12.3. Bioaccumulative potential

No information available.

Partition coefficient No information available

12.4. Mobility in soil

**LEATHER ADHESIVE 20ML FILLED TUBE** 

Supercedes Date: 19-Dec-2016

Revision Date 03-Sep-2018 Revision Number 1.01

Mobility in soil No information available.

#### 12.5. Results of PBT and vPvB assessment

. The components in this formulation do not meet the criteria for classification as PBT or vPvB.

Chemical Name	PBT and vPvB assessment
Methyl ethyl ketone	The substance is not PBT / vPvB
78-93-3	
Acetone	The substance is not PBT / vPvB
67-64-1	
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW	The substance is not PBT / vPvB
25068-38-6	

#### 12.6. Other adverse effects

No information available

#### **Endocrine Disruptor Information**

.

Chemical Name	EU - Endocrine Disrupters Candidate List	EU - Endocrine Disruptors - Evaluated Substances
Bisphenol-A-Epichlorhydrin Epoxy resin <= 700 MW 25068-38-6	Group III Chemical	

## Section 13: DISPOSAL CONSIDERATIONS

#### 13.1. Waste treatment methods

Waste from Residues/Unused

**Products** 

Dispose of wastes in an approved waste disposal facility.

Contaminated Packaging Improper disposal or reuse of this container may be dangerous and illegal.

**European Waste Catalogue** 08 04 09\* waste adhesives and sealants containing organic solvents or other dangerous

substances

Other Information Waste codes should be assigned by the user based on the application for which the

product was used.

## Section 14: TRANSPORT INFORMATION

Land transport (ADR/RID)

**14.1 UN Number** UN1133 **14.2 Proper Shipping Name** Adhesives

14.3 Transport hazard class(es) 3 Labels 3 14.4 Packing Group III

**Description** UN1133, Adhesives, 3, III

14.5 Environmental hazards Not applicable

14.6 Special Provisions 640E
Classification Code F1
Tunnel restriction code
Limited Quantity (LQ) 5 L
ADR Hazard Id (Kemmler 30

Number)

**IMDG** 

**14.1 UN Number** UN1133 **14.2 Proper Shipping Name** Adhesives

**14.3 Transport hazard class(es)** 3 **14.4 Packing Group** III

**LEATHER ADHESIVE 20ML FILLED TUBE** 

Supercedes Date: 19-Dec-2016 Revision Number 1.01

**Description** UN1133, Adhesives, 3, III, (-20°C c.c.)

 14.5 Marine Pollutant
 Np

 14.6 Special Provisions
 223, 955

 Limited Quantity (LQ)
 5 L

 EmS-No.
 F-E, S-D

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information available

#### Air transport (ICAO-TI / IATA-DGR)

**14.1 UN Number** UN1133 **14.2 Proper Shipping Name** Adhesives

**14.3 Transport hazard class(es)** 3 **14.4 Packing Group** III

**Description** UN1133, Adhesives, 3, III

14.5 Environmental hazards Not applicable

14.6 Special Provisions A3 Limited Quantity (LQ) 10 L ERG Code 3L

## Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **European Union**

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

## Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

## EU-REACH (1907/2006) - Candidate List of Substances of Very High Concern (SVHC) for Authorization in accordance with Article 59

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

#### EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

#### EU-REACH (1907/2006) - Annex XIV - List of substances subject to Authorization

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Dangerous substance category per Seveso Directive (2012/18/EU)
P5a - FLAMMABLE LIQUIDS

or

P5b - FLAMMABLE LIQUIDS

Revision Date 03-Sep-2018

or

P5c - FLAMMABLE LIQUIDS

## Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

### **Persistent Organic Pollutants**

**LEATHER ADHESIVE 20ML FILLED TUBE** 

Supercedes Date: 19-Dec-2016

Revision Date 03-Sep-2018 Revision Number 1.01

No. 12 11

Not applicable

## 15.2. Chemical safety assessment

## Section 16: OTHER INFORMATION

## Key or legend to abbreviations and acronyms used in the safety data sheet

#### Full text of H-Statements referred to under section 3

H315 - Causes skin irritation

H319 - Causes serious eye irritation

H317 - May cause an allergic skin reaction

H411 - Toxic to aquatic life with long lasting effects

H336 - May cause drowsiness or dizziness

H225 - Highly flammable liquid and vapour

EUH066 - Repeated exposure may cause skin dryness or cracking

#### Legend

SVHC: Substances of Very High Concern for Authorisation:

**Legend** SECTION 8: Exposure controls/personal protection

TWA TWA (time-weighted average) STEL STEL (Short Term Exposure Limit)

Ceiling Maximum limit value \* Skin designation

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals STOT (RE): Specific target organ toxicity - Repeated exposure STOT (SE): Specific target organ toxicity - Single exposure

EWC: European Waste Catalogue

#### Key literature references and sources for data

Classification and labeling data calculated from data received from raw material suppliers

Prepared By Product Safety & Regulatory Affairs

Revision Date 03-Sep-2018

Indication of changes

Revision Note Not applicable.

**Training Advice** Provide adequate information, instruction, and training for operator

Further information No information available

This material safety data sheet complies with the requirements of Regulation (EC) No. 1907/2006

### **Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**End of Safety Data Sheet**