


ART & CRAFT WHITE GLUE

A SOLVENT FREE CRAFT ADHESIVE

TECHNICAL DATA SHEET

SMART ADVANTAGES

- ACID FREE, IDEAL FOR SCRAP BOOKING
- CLEAR DRYING, INVISIBLE GLUE LINE
- SOLVENT FREE, NON TOXIC, SAFE FOR KIDS



Bostik

White Glue

DESCRIPTION

Bostik Art & Craft White Glue is a polyvinyl acetate based adhesive, which has been developed to provide superior performance for art and crafts projects where it bonds a wide variety of substrates and dries to a clear non-visible glue-line.

APPLICATIONS

Ideal home, office and school, where it can be used for art and crafts, scrap booking, photo albums, school projects, handicraft and decorative work, greeting cards, invitation, paper decorations, paper mache, mounting pictures, decoupage, etc. Can be mixed with powder paints for finger painting.

ADHESION

Excellent adhesion to porous materials such as fabric, leather, paper, textiles, felt, wood, cardboard, cellophane, photographic paper, and cork. Fair adhesion of above materials to metals and glass.

LIMITATIONS

- One surface must be porous.
- Not suitable for bonding plastics and some coated papers e.g. wax coated, polyethylene laminated paper.

SAFETY INSTRUCTIONS

Bostik Art & Craft White Glue is non-toxic. Avoid contact with eyes. In the event of skin or eye contact, rinse thoroughly and immediately with water. Seek medical assistance if irritation or discomfort persists. Keep out of reach of small children! Refer to our Safety Data Sheet for further toxicological information and comprehensive handling instructions.

SURFACE PREPARATION

Ensure that surfaces are clean and dry.

HOW TO USE

- 1. Apply glue to one surface.
- 2. Press pieces together and allow to dry (approx. 1 minute to 1 hour, depending on substrate).
- 3. Clean any spills with a damp cloth.
- 4. Remove excess glue from nozzle and replace cap.

CLEANING

Clean with warm soapy water.

STORAGE STABILITY

Bostik Art & Craft White Glue has a shelf life of at least 18 months if stored in a cool (below 25°C), dry place in its original moisture-tight container. If the material is kept beyond the recommended shelf life, it is not necessarily unusable. A check should be performed to observe whether the product has not separated, thickened, or shows signs of bacterial degradation (bad smell, discoloration and low viscosity).



PRODUCT PACKAGING

• 100ml Bottle

PRODUCT CHARACTERISTICS	
Appearance	White viscous liquid
Density (g/cm ³)	Approximately 1.06 g/cm ³
Odour	Slightly sweet
Solids (%)	Approximately 38%
Viscosity (cPs)	Approximately 13 000
TYPICAL PERFORMANCE DAT	Ā
Drying time	1min – 60min (depending on environmental conditions & substrates)

DISCLAIMER

Water resistance

The above information is only offered as a guide to the use of this product. Furthermore, users should satisfy themselves that it is suitable for their needs. Since we have no control over the conditions under which it is used, we cannot accept responsibility for the problems caused by the use and/or application of this product.

Poor

Head Office: +27(0)21 555 7400 Beverley Close, Montague Gardens, 7441 PO Box 37008, Chempet, 7442 www.bostik.co.za

ASK A STICKY QUESTION... www.stickyquestions.co.za 0800 222 400

