

# **Bostik Clear Gel Adhesive**

# SAFETY DATA SHEET

# 1. IDENTIFICATION

#### 1.1. Product identifier

Product name Bostik Clear Gel Adhesive
Chemical family Nitrile rubber solution

#### 1.2. Intended use of the product

All-purpose clear non-drip adhesive for use in the home, office and school

# 1.3. Name, address, and telephone of the responsible party

Company Permoseal (PTY) Ltd

Address 1 Beverley Close, Montague Gardens, 7441, Cape Town, South Africa

 Phone
 +27-21-555-7400

 Toll-free No.
 0800-222-400

 Website
 www.bostik.co.za

# 1.4. Emergency phone number

+27-21-555-7400

# 2. HAZARDS IDENTIFICATION

# 2.1. Classification of the substance or mixture

GHS Classification This product is hazardous

#### 2.2. Label elements

# **GHS** Labelling

- This product is classified and labelled according to the CLP regulation.
- Hazard pictogram:





GHS02

GHS07

# 2.3. Signal word

Danger

# 2.4. Hazard determining components of labelling:

Acetone, Methyl Ethyl Ketone

#### 2.5. Hazard statements:

H225 Highly flammable liquid and vapour

H315 Causes skin irritation

H319 Causes serious eye irritation
H335 May cause respiratory irritation
H371 May cause damage to organs
H336 May cause drowsiness or dizziness



#### 2.6. Precautionary statements:

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P280 Wear protective gloves / eye protection.
P273 Avoid release to the environment.
P201 Obtain special instructions before use.

P308+P313 If exposed or concerned: get medical advice/attention.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy

to do. Continue rinsing.

#### 2.7. Other Hazards

No further data available

#### a. Unknown acute toxicity

No data available

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Mixture. This product is hazardous.

Ingredient	CAS No.	Contents (%)	Classification of Substance
Acetone	67-64-1	50 - 70	Flam liq.: Cat 2 Eye Irritation: Cat 2 STOT SE: Cat 3
Methyl Ethyl Ketone	78-93-1	5 - 15	Flam liq.: Cat 2 Eye irritation: Cat 2 STOT SE: Cat 3

# 4. FIRST- AID MEASURES

#### 4.1. Description of first aid measures

General Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice.

Inhalation Move to fresh air and seek medical attention if nausea and dizziness persists. Aspiration into lungs

may lead to pneumonitis.

Skin contact Wash skin with mild soap and water. Remove contaminated clothes and shoes. Seek medical

attention.

Eye contact Remove any contact lenses from the eyes before rinsing thoroughly with plenty of water (lift eye lids).

Rinse for at least 15 minutes. Seek medical attention if any discomfort continues.

Ingestion Rinse mouth. Do not induce vomiting. Get the affected person to drink a lot of water in small gulps.

Obtain medical attention.

#### 4.2. Most important symptoms and effects both acute and delayed

General May cause irritation.

Inhalation May cause irritation to the respiratory system. Prolonged inhalation may cause headaches,

drowsiness and fatigue. High concentrations of vapours are anaesthetic in nature causing central

nervous system effects such as dizziness and confusion.

Skin contact May cause skin irritation – Prolonged contact can cause defatting and drying of the skin which may

result in a burning sensation and a dried, cracked appearance. Repeated exposure may lead to

dermatitis.

Eye contact May cause eye irritation – can cause redness, tearing and blurred vision due to corneal clouding.

Ingestion Hazardous – may be fatal if swallowed.

#### 4.3. Indication of any immediate medical attention and special treatment needed



#### 5. FIRE-FIGHTING MEASURES

5.1. Extinguishing media

Suitable extinguishing media Water spray, dry chemical powder, foam, carbon dioxide

Unsuitable ext.media Not applicable

5.2. Special hazards arising from the substance or mixture

Fire hazard Highly flammable

Explosion hazard Solvent vapour may form explosive mixtures with air

5.3. Advice for firefighters

Protection during firefighting Firefighters should wear full protective gear. Do not enter fire area without proper protective

equipment, including respiratory protection.

Hazardous combustion products Under certain conditions of combustion, traces of toxic substances cannot be excluded.

# 6. ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal precautions, protective equipment and emergency procedures

General measures Do not get in eyes or skin, or on clothing.

6.2. For non-emergency personnel

Emergency procedures Evacuate unnecessary personnel.

6.3. For emergency personnel

Protective equipment Use appropriate personal protection equipment (PPE)

Emergency procedures Secure the area and evacuate unnecessary personnel.

6.4. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters.

#### 6.5. Methods and materials for containment and cleaning up

For containment Absorb and or contain spill with inert material.

Dispose of in accordance with current local legislation.

#### 6.6. Reference to other sections

Refer to Section 8, Exposure controls and personal protection

### 7. HANDLING AND STORAGE

## 7.1. Precautions for safe handling

Handling temperature Normal ambient temperature

Hygiene measures Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other

exposed areas with mild soap and water before eating or drinking.

# 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions Store in a dry, cool and well-ventilated place away from heat, sparks, open flames and any other

ignition sources. Keep container closed when not in use.

Incompatible materials Strong oxidizing agents

Maximum storage period 12 months, but may vary depending on storage conditions.

# 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

# 8.1. Control parameters

Exposure limits:

Name	TWA - 8 hrs	STEL - 15 min
Acetone	750ppm	1500ppm
Methyl Ethyl Ketone	200ppm	300ppm



#### 8.2. Exposure controls

Engineering controls Provide good ventilation when handling large quantities. No special measures are required

if stored and handled as above. Ventilation must be explosive proof.

Eye protection Normally not needed for domestic use. Industrial uses require safety glasses.

provide sufficient protection.

approved respirator if there is potential to exceed exposure limits.

Other information When using, do not eat or drink.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Clear gel Odour Aromatic

Density (g/cm³ @20°C)

Flash point (°C)

Boiling point (°C)

Approximately -18

Approximately 56

Flammability limits (%)

2.0 – 13.3

Solubility water

Insoluble

Solubility solvent Soluble in esters, ketones and methanol

#### 10. STABILITY AND REACTIVITY

Reactivity Prolonged exposure to air will result in solvent evaporation and gelation of product.

Chemical stability Stable under normal conditions.

Possibility of hazardous reactions 
Not expected under normal conditions.

Conditions to avoid Avoid temperature extremes, open flames, sparks or other possible ignition sources.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition products Thermal decomposition may release carbon dioxide, carbon monoxide, smoke and fumes.

# 11. TOXICOLOGICAL INFORMATION

The toxicological properties of this product have not been fully investigated. Please refer to section 4 for information regarding health effects.

### 12. ECOLOGICAL INFORMATION

This product has not been tested for environmental effects. However, the ingredients indicate that it is dangerous to the environment. Please refer to section 6 for information regarding accidental release.

### 13. DISPOSIBLE CONSIDERATIONS

Sewage disposal recommendations Do not dispose waste into sewer.

Waste disposal recommendations Whatever cannot be saved for recovery or recycling should be disposed of in accordance

with current local legislation



# 14. TRANSPORT INFORMATION

#### 14.1 UN Number

ADR, ADN, IMDG, IATA UN 1133

# 14.2 UN Proper Shipping Name

• ADR/AND, IMDG, IATA Flammable liquid, N.O.S.

#### 14.3 Transport hazard class

ADR, ADN, IMDG, IATA LABEL



CLASS 3 Flammable liquids

# 14.4 Packing group

ADR, ADN, IMDG, IATA

#### 14.5 Environmental hazards

Marine pollutant (IMDG), Special marking (ADR/AND), Special marking (IATA)
 Contamination of the aquatic or terrestrial environments should be avoided.

#### 15. REGULATORY INFORMATION

15.1 Labelling Classified as a hazardous product

15.2 National legislation None

#### **16. OTHER INFORMATION**

#### 16.1 Information sources

This SDS is prepared based on the information received from the suppliers

# 16.2 Full text of H-phrases referred to under Section 3

H225 Highly flammable liquid and vapour

H315 Causes skin irritation

H319 Causes serious eye irritation
H335 May cause respiratory irritation
H371 May cause damage to organs
H336 May cause drowsiness or dizziness

#### 16.3 Additional information

This document has been prepared in accordance with the SDS requirements of SANS 11014:2010

For intended use and applications see the Technical Date Sheet for the product. The information provided in this Safety Data Sheet is based on the present state of our knowledge. This data is intended to enable safety assessments to be made and should not be construed as guaranteeing specific properties. Recipients of our product must take responsibility for observing existing laws and regulations.

Revision date November 2016

