

Super Clear Tape

SUPER TRANSPARENT

TECHNICAL DATA SHEET

SMART ADVANTAGES

- TRANSPARENT, VIRTUALLY INVISIBLE ON PAPER
- REMOVABLE WITHOUT STAINING
- RESISTANT TO AGING, NON-YELLOWING
- ACID FREE, IDEAL FOR SCRAP BOOKING

DESCRIPTION

Bostik Super Clear Tape is a pressure-sensitive tape manufactured with biaxial orientated polypropylene film coated with water-based acrylic adhesive. The tape exhibits an excellent balance of tack and peel properties to give optimum adhesive strength. Bostik Super Clear Tape is available in two formats, a twin pack 12mm x 33m dispenser and a twin pack 18mm x 20m dispenser.

APPLICATIONS

Ideal home, office and school work, where it can be used for gift wrapping, sealing of boxes, holding up posters, art and crafts, scrap booking, photo albums, handicraft, decorative work and temporary repairs.

ADHESION

Bostik Super Clear Tape bonds to most materials like paper, card, foil, glass, metal, wood and plastics.

LIMITATIONS

- Not for heavy duty use.
- May damage fragile papers on removal.
- Not suitable where heat resistance is required.

SAFETY INSTRUCTIONS

Use dispenser with caution as it contains a sharp edge. Keep out of reach of small children! Does not contain natural rubber latex.

SURFACE PREPARATION

Ensure that surfaces are clean, dry and free of any dust, grease and loose materials.

HOW TO USE

1. Pull tape to desired length and cut to desired length or with the serrated edge of the dispenser.
2. Apply to surfaces and press firmly over the entire area.



CLEANING

Easily removed from most surfaces. Adhesive residue can be removed with acetone from non-porous surfaces.

STORAGE STABILITY

The shelf life of the product is 36 months when stored at room temperature.

PRODUCT PACKAGING

- Bostik Super Clear Tape Value Pack – 2 x (12mm x 33m)
- Bostik Super Clear Tape Dispenser Value Pack – 2 x (18mm x 20m)

PRODUCT CHARACTERISTICS

Appearance	Clear sticky tape
Film type	Biaxial orientated polypropylene
Film thickness	Approximately 50u (28u film, 22u glue)
pH	7 – 8

TYPICAL PERFORMANCE DATA

Temperature resistance	poor
Tack (N/cm)	≤ 5.0 (25°C, RH 62%)
Peel Adhesion (180°)	≥ 6.0 (25°C, RH 62%)
Water resistance	Good

DISCLAIMER

The above information is only offered as a guide to the use of this product. Furthermore, users should satisfy themselves that it is suitable for their needs. Since we have no control over the conditions under which it is used, we cannot accept responsibility for the problems caused by the use and/or application of this product.

Head Office: +27(0)21 555 7400
 Beverley Close, Montague Gardens, 7441
 PO Box 37008, Chempet, 7442
www.bostik.co.za

ASK A STICKY QUESTION...
www.stickyquestions.co.za
0800 222 400

