



Super Glue Easy Flow Liquid

CYANOACRYLATE ADHESIVE IN A BOTTLE

Date: 7 January 2019

Fact Sheet No.: TDS00083

YOUR SMART ADVANTAGES

- Ultra strong
- Fast setting: Bonds in seconds
- Controlled flow

USES

Bostik Super Glue Easy Flow Liquid is a high strength, fast setting solvent free adhesive which can be used for virtually any type of fastening job and bonds in seconds without the need for heat or clamps.

Bostik Super Glue Easy Flow Liquid has been formulated to achieve the strongest possible bond between non-porous materials such as wood, rubber, metal, ceramics, hard plastics, leather and much more.

PRODUCT CHARACTERISTICS

Colour	Clear
Form	Thin liquid
Specific Gravity	1.1 approx.
Composition	Ethyl Cyanoacrylate
Product Code	30803655 5ml bottle on blister x 6 30611518 20ml bottle on blister x 6
Storage/Shelf Life	Store for up to 12 months from date of manufacture when stored in original, unopened packaging in a cool, dry place 20-25°C. For long term storage, refrigeration (5°C) is recommended.

TYPICAL PERFORMANCE DATA (Approx.)

Working Temperature	-55°C to +80°C.
---------------------	-----------------

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Super Glue Easy Flow Liquid refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

PREPARATION

1. Read all instructions carefully before use.
2. Work on a protected surface as any spillages are very difficult to remove, particularly for sensitive surfaces like fabrics and skin.
3. Make sure all surfaces to be bonded are clean and dry, being free from dirt and grease.
4. Always point the bottle away from you when opening and don't squeeze.

APPLICATION

5. Remove the cap by unscrewing it. The bottle is then ready to use.
6. Avoiding skin contact, apply a small amount of Bostik Super Glue Easy Flow to one surface.
7. Press the surfaces together and hold for a few seconds until the glue sets.
8. After use, wipe the nozzle with a cloth and replace the cap. Store the bottle upright in a cool, dark place.

CLEANING

9. Bostik Super Glue Easy Flow has good resistance to most oils and solvents and can be very difficult to remove.
10. Bostik Super Glue Easy Flow Liquid bonds to skin very quickly and easily. Should this happen, please do not panic. Do not attempt to pull apart as this may damage the skin. If left the bond will loosen within 60 minutes

without doing anything. Hot soapy water and gentle peeling will part the bond, this can take 10 minutes.

11. Acetone will very slowly soften set super glue. Before attempting its use check that it is safe to use a highly flammable solvent and that the surfaces to which the super glue is adhered are not damaged by the solvent. Do not use acetone or solvents on the skin.
12. Always test before using any solvent.

PRECAUTIONS IN USE

Protect work surface. Product won't work on soft plastics like polythene, or absorbent surfaces like paper. Don't use for objects that hold hot food/liquids or high-stress joints.

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.co.uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data Sheet for Bostik Super Glue Easy Flow, available at www.bostik.com/uk

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Technical Data & Safety Data Sheets	Tel: 01785 272625	Fax: 01785 212962	sds.box-eu@bostik.com