



Hard Plastics Adhesive

A WATER RESISTANT ADHESIVE

Date: 20 July 2018

FactSheet No.: TDS00469

YOUR SMART ADVANTAGES

- Extra strong
- Quick drying
- For tough repairs

USES

Bostik Hard Plastics Adhesive is a solvent-borne adhesive based on SBS polyurethane. It has the advantages of easy application, by comb or brush and immediate strength on contact.

Bostik Hard Plastics Adhesive is suitable for bonding the following plastics to themselves and each other: PVC-U, ABS, High Impact Polystyrene. It has a wide range of uses for repairing household objects. Bostik Hard Plastics Adhesive is also useful for sticking most clear plastics, wood, metal and leather.

PRODUCT CHARACTERISTICS

Colour	Transparent
Form	Mobile liquid
Specific Gravity	0.92 approx.
Composition	Synthetic resin
Product Code	30803651 20ml x 6 blister cards
Storage/Shelf Life	Store for up to 24 months when stored in the original, unopened packaging under dry conditions within the temperature range of +5°C to +25°C.

Solids Content	27% approx.
Viscosity	Low
Odour	Ketonic
TYPICAL PERFORMANCE DATA (Approx.)	
Application Temperature	+5°C to +30°C
Flammability	Highly flammable
Service Temperature	-20°C to +60°C
Water Resistance	Good

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Hard Plastics Adhesive refer to the relevant Health & Safety Data Sheet, available at www.bostik.co.uk.

PREPARATION

1. Make sure that the surfaces to be bonded are clean and dry, being free from dust, dirt and grease.

APPLICATION

2. Remove tube cap and spread the adhesive evenly over both surfaces.
3. Leave the coated surfaces until the adhesive is just tacky - approximately 4 minutes at normal room temperatures.
4. Ensure the surfaces are accurately aligned and then press them firmly together. They will stick immediately.

CLEANING

5. Bostik Hard Plastics can be removed using nail polish remover or acetone before set. Solvents can damage some surfaces therefore carry out a test to be certain.

PRECAUTIONS IN USE

Bostik Hard Plastics Adhesive is not suitable for polyolefin's e.g. polythene, polypropylene or PTFE. It should not be used for repairing items that hold hot liquids.

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.co.uk for advice.

Recommendation and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data Sheet for Bostik Hard Plastics Adhesive, available at www.bostik.co.uk.

BOSTIK HOTLINE

Smart help +44 (0) 1785 272625



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Safety Data Sheets	Tel: 01785 272625	Fax: 01785 212962	sds.box-eu@bostik.com