



# BOSTIK SUPER GLUE MINIS

## INDUSTRIAL STRENGTH

30<sup>th</sup> July 2020

### YOUR SMART ADVANTAGES

- Dries clear
- Fast drying
- Solvent free
- Exceptional tensile strength up to 450Kg per cm<sup>2</sup>
- Enables precision work due to its small size

### DESCRIPTION

Bostik Super Glue is a multipurpose glue that bonds most non-porous material in seconds. It dries to a clear, permanent bond with exceptional tensile strength up to 450Kg per cm<sup>2</sup>. Its small format makes it perfect for one job around the home and office, without any dry out concerns.

### USES

Bostik Super Glue bonds materials such as china, metals, ceramics, rubber, and most plastics – (not polyethylene or polypropylene).

Bostik Super Glue can be used as an instant adhesive for a multitude of “Fix-It” situations. Because of its packaging and small size, it is an excellent choice for precision work in industries such as electrical, optical, watch and jewellery and car accessories etc.

### PRODUCT CHARACTERISTICS

Colour	Clear
Physical Form	Translucent/Clear thin liquid
Chemical Type	Ethyl Cyanoacrylate
Solids Content	100%
Odour	Slightly acrid – odourless when cured
Specific Gravity	1.10 approx
Flash Point	80 – 93 °C
<b>Product codes</b>	
1ml x 3 Blister	30617845

### DIRECTIONS FOR USE:

**IMPORTANT:** Before using Bostik Super Glue Minis, refer to the relevant Safety Data Sheet, available at [www.bostik.com.au](http://www.bostik.com.au)

### APPLICATION

1. Make sure that the surfaces to be bonded are clean, dry and free from dust, dirt, grease and any other contaminants.
2. Unscrew entire cap assembly and carefully pierce a small hole in the metal tube with the reverse end of cap. Replace cap immediately.

### APPLICATION

3. Apply one drop or smallest amount possible to one surface, as a thin film gives best and strongest results. **DO NOT SPREAD:** Super Glue will spread/level itself.
4. Press both surfaces together and firmly hold for a few seconds – good contact is essential. *Note:* Maximum bond strength achieved in 24 to 48 hours (in most instances, an adequate bond develops in less than one minute).

### CLEANING

5. Wipe off excess with cloth, making sure that both substrates are well matched and tight fitting.
6. After completion of job, wipe tip of plastic nozzle, replace cap tightly and store in a cool upright position.

### PRECAUTIONS IN USE

1. Use in a well-ventilated area.
2. To avoid adhesive whitening, do not apply in hot temperatures or high humidity and ensure that vapours can escape.
3. Not recommended on paper, plastics with an oily/waxy appearance e.g. polyethylene, polypropylene or Teflon. Will not permanently bond glass or materials containing a high alkaline content.

### STORAGE AND SHELF LIFE

Store in a cool dry place between +5 to +25° C and out of direct sunlight. Shelf life is 12 months from the date of manufacture when stored as directed in its original, unopened packaging. Temperatures less than 2 °C can adversely affect product properties. **DO NOT FREEZE.**

# BOSTIK SUPER GLUE MINIS

## HEALTH & SAFETY

Cyanoacrylate - bonds skin and eyes in seconds. Keep out of the reach of children. Read label before use.

IN CONTACT WITH EYES. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If medical advice is needed, have product container or label at hand.

Always read the Technical Data Sheet and Safety Data Sheet (SDS) before handling or use. Full product safety information required for safe use is not included in this data sheet. SDS available by request or at [www.bostik.com.au](http://www.bostik.com.au)

Recommendations and suggestions are for guidance only, since conditions of use are completely out of our control.

**For emergency information contact the Poisons Information Centre, phone 131 126 or the Emergency Response Service, phone 1800 033 111.**

BOSTIK HOTLINE

Smart help 1800 267 845



This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out of date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation, for example under the Australian Consumer Law (ACL). Sale of the product by Bostik is subject to the Bostik Australia Proprietary Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit [www.bostik.com/au](http://www.bostik.com/au)