

Glu GO

ADHESIVE REMOVER

TECHNICAL DATA SHEET

SMART ADVANTAGES

- REMOVE ADHESIVES & CHEWING GUM
- NON DRIP GEL FORMULA
- MULTI SURFACE APPLICATION

DESCRIPTION

Bostik Glu GO is a viscous hydrocarbon based adhesive remover formulated for the fast, and easy removal of sticky, gummy adhesive residue from non-porous surfaces and some fabrics. The gel formula is non drip and holds to surfaces allowing the proprietary solvent and surfactant blend to penetrate the adhesive residue. Bostik Glu GO acts by softening the adhesive residue allowing for its easy removal. Effective on a wide variety of adhesive and sealant technologies, including solvent based and urethane adhesives. Removes Contact Adhesive, Prestik, wax, chewing gum, correction fluid and tacky residues from labels and tapes. Has a mild solvent odour with a citrus undertone.

APPLICATION

- Removes all sticky labels, plasters, decals, tapes, double sided tapes and most adhesive residue from metal, glass, painted walls, tiles, laminated woods (Melamine & Formica®), painted woods (doors), plastic bottles, containers etc.
- Removes a wide variety of adhesives and putties such as Prestik, wax, chewing gum and most other tacky residues from hard surfaces.
- Removes sticky, gummy residue from carpets and most fabrics.
- Removes cured Contact Adhesive, bitumen, grease, tar and asphalt from non-porous surfaces.
- Removes correction fluid (Tippex®) from most fabrics, laminated woods, glass and some plastics.
- Removes hardened mastics and other adhesives that remain after old floor coverings such as carpet and linoleum have been removed.



LIMITATIONS

- Not suitable for the removal of some cured reactive adhesives i.e. cyanoacrylate (super glue), epoxy and silicone and water based adhesives
- Avoid contact with varnished and wax surfaces.
- May affect some metal, plastics, and fabrics i.e. Nylon. We recommend testing a small inconspicuous area prior to application to ensure the surface is unaffected. May affect colour in certain fabrics. Test for colour fastness before using.
- Not suitable as a hand cleaner, skin contact should be avoided.
- Not suitable for porous surfaces i.e. unsealed natural stone since this may wash the residue deeper into the pores.

SAFETY INSTRUCTIONS

Bostik Glu GO is flammable. Always work in a ventilated area. Do not breathe in vapours. Avoid exposing product to any source of ignition. Do not smoke when working with Bostik Glue GO. It is advisable to wear gloves in order to avoid direct contact with skin. If product comes into contact with skin or eyes, rinse thoroughly and immediately with water as the product will dry out the skin. Seek medical attention if irritation or discomfort persists. Keep out of reach of children! Refer to our Safety Data Sheets for further toxicological information and comprehensive handling instructions.

SURFACE PREPARATION

- This product can be used on walls and other vertical surfaces as it is a non-drip gel formula.
- Always apply Bostik Glu GO on a small inconspicuous area first to test for suitability on the surface before using.

HOW TO USE

1. Remove cap from tube and pierce seal with reverse side of cap.
2. Apply a thick layer of Bostik Glu GO to the desired area using the scraper and leave for 10 - 30 minutes, (depending on thickness, size, type and age of the adhesive being removed). Fresh uncured glue spills can be wiped off almost immediately.
3. Remove the softened adhesive with a cloth, hard plastic scraper or spatula.
4. A second to third application may be required, depending on the thickness and age of the residue.
5. Covering with a plastic sheet to keep a longer contact time with Bostik Glu Go will enhance performance.
6. Once the adhesive residue has been removed, wash the surface with soap and water.
7. Close lid to avoid product drying out and rinse scraper and utensils after application.
8. For best results, used on fresh uncured glue spills and those that are less than 24 hours old.

APPLICATION TABLE

ADHESIVES	RESULT
Acrylic(tape, foam tapes, labels)	Excellent
Correction Fluid (Tippex®)	Excellent
Bitumen	Excellent
Prestik	Excellent
Chewing Gum	Excellent
Candle Wax	Excellent
Nitrile Rubber (Clear Adhesive)	Good
Polychloroprene(Contact Adhesive)	Good
Nails Polish	Good
Ink (Pen Marks)	Average
PVA (Cold Glue)	Not Suitable
Wood Glue	Not Suitable
Hot Melt Glue	Not Suitable
Silicone*	Not Suitable
Cyanoacrylate(Super Glue)**	Not Suitable

* use Bostik Silicone Stripper ** use acetone

STORAGE STABILITY

Bostik Glu GO has a shelf life of at least 12 months if stored in a cool (below 25°C), dry place in its original moisture-tight container. If the material is kept beyond the recommended shelf life, it is not necessarily unusable, but a check should be performed to observe whether the product is still workable. Keep product sealed at all times as it will dry out inside the tube if left open for long periods at a time.

PRODUCT PACKAGING

- 90ml Tube

PRODUCT DATA	
Appearance	Opaque viscous gel
Softening time	Approx. 10 - 30 min (depending on thickness, type and age of adhesive)

DISCLAIMER

The above information is only offered as a guide to the use of this product. Furthermore, users should satisfy themselves that it is suitable for their needs. Since we have no control over the conditions under which it is used, we cannot accept responsibility for the problems caused by the use and/or application of this product

Head Office: +27(0)21 555 7400
 Beverley Close, Montague Gardens, 7441
 PO Box 37008, Chempet, 7442
 diy.bostik.com/en-ZA

ASK A STICKY QUESTION...
www.stickyquestions.co.za
0800 222 400

