



GLU DOTS EXTRA STRONG

SMALL ADHESIVE DOTS

TECHNICAL SHEET 17/08/2023

YOUR SMART ADVANTAGES

- Instant bond
- Double-sided
- Acid and lignin free
- Translucent colour
- Permanent hold

DESCRIPTION

Bostik Glu Dots Extra Strong are individually formed translucent dots of pressure sensitive adhesive, which have a very high tack. They are safe, simple to use, acid and lignin free, and non-yellowing.

RECOMMENDED USES

Ideal for bonding vertical surfaces, and can substitute many other methods of fixing such as messy liquid adhesives, glue sticks, and hot melt glue guns.

Bostik Glu Dots Removable are the perfect size to allow for precise and accurate placing of small objects such as sequins, beads, rhinestones, wiggly eyes, and many other craft embellishments.

Bostik Glu Dots Removable stick to almost anything, including paper, wood, plastic, metal, and glass.

PRODUCT CHARACTERISTICS

Composition	Hydrocarbon Polymer
Colour	Transparent
Form	Sticky adhesive dots
Specific Gravity	1.0 approx.
Pack Quantity	64 dots



DIRECTIONS FOR USE

Read and understand the Safety Data Sheet before using this product. SDS can be acquired by visiting www.bostik.com/australia.

Always test Bostik Glu Dots Extra Strong on an unseen area of your materials prior to application.

Not suitable for use on damp, delicate, absorbent or newly decorated surfaces. Not recommended for application to painted plaster walls.

Recommendations and suggestions are for guidance only, since conditions of use are out of our control.

SURFACE PREPARATION

1. Ensure surfaces are clean; dry free from grease and loose materials.
2. For best results, surfaces and surroundings should be pleasantly warm.
3. Take out a sheet of dots from the wallet.
4. Fold and then tear off, along the perforations, to remove as many dots as required.

APPLICATION

5. Peel off the printed release paper to reveal a Glu Dot left on the clear backing. The Glu Dot is now ready for use.
6. Press the Glu Dot firmly onto the item to be bonded and then slowly and carefully peel off the clear backing.
7. The Glu Dot will be adhered to the item, which can now be bonded to the other surface.

CLEANING

When newly attached, dots may be removed by carefully and very slowly peeling away from the surface. As the adhesive gets stronger with time, we recommend taking extra caution if removal is required.

SHELF LIFE & STORAGE

24 months, unopened, from date of manufacture. Store in dry conditions between +5° C and +25° C

SAFETY

Always read the Technical Data Sheet and Safety Data Sheet (SDS) before handling or use. Full product safety information required for safe use is not included in this data sheet. SDS available by request or at www.bostik.com.au

DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contain herein.

Bostik Australia
51-71 High St
Thomastown, VIC
P: 1800 BOSTIK (267 845)
www.bostik.com.au

BOSTIK HOTLINE

Smart help 1800 267 845



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.