



BL 50

MULTI-PURPOSE LUBRICANT

TECHNICAL DATA SHEET

YOUR SMART ADVANTAGES

- Unfastening rusted joints, nuts and bolts
- Sustainable protection against corrosion
- Grease and lubrication for runners, joints, hinges, chains
- Removing squeaking and creaking noises
- Cleaning and stripping
- Driving out moisture from finest cracks and seams
- Germany made

DESCRIPTION

Bostik BL 50 is a thin fluid oil spray for lubrication and maintenance of metal parts. Suitable for automotive and engineering, locksmith, crafts and households. Bostik BL 50 is silicone-free.

PRODUCT CHARACTERISTICS

Color	Transparent
Base	Hydrocarbons
Density	Approx. 0.819
Extrusion rate gs.	Approx. 1.9
Frost resistance during transportation	Up to -15°C
Pressure at 20°C bar	6.2
Pressure at 50°C bar	8.1

*These are typical values

DIRECTION FOR USE

Shake the aerosol vigorously before use. Clean and degrease the surface to be treated, then spray it from a distance of approx. 20-30cm and rub the substance in with a soft cloth.

APPLICATION

Penetrates threads, lubricates hinges, coils, springs, water-taps, windows and door-handles, swivel chairs, etc. Suppresses humidity on metal surfaces, e.g. electrical contacts, car ignitions, tools, motorbikes and outboard engines.

Cleans.

Removes paint stick stains, grease, tar, rubber and adhesive residues. Loosens rusty parts. Penetrates deeply and loosens rusty, fretted and stuck nut bolts, screws, switches, wires and other locks.

Protects.

Leaves a protective film against rust, corrosion of bicycles, pushchairs, chrome parts, motorbikes, outboard engines and tools. Loosens stuck mechanical fixtures, loosens and greases door locks, hinges, zippers, sewing machines, switches, couplings and wires.

PACKAGING

Aerosol can

STORAGE AND SHELF LIFE

Store between +5°C and +25°C in shaded conditions. Shelf life is 24 months when stored as recommended in original unopened packaging.

HEALTH & SAFETY

Always read the Technical Data Sheet and Safety Data Sheet (SDS) before handling or use. Full product safety information required for safe use is not included in this data sheet. SDS available by request.

PRECAUTION IN USE

Recommendations and suggestions are for guidance only, since conditions of use are completely out of our control.

This datasheet is for the general help of users. It is provided in good faith. The data is current and accurate to the best of our knowledge. Differing materials, substrates, environments, site conditions, and product storage, handling and application may affect results. Users should carry out tests to decide the product's suitability for purpose. This data sheet and the properties of the product may change without notice. Users, suppliers and retailers should check that the data sheets they have are the latest. To the maximum extent permitted by law, Bostik disclaims all warranties in relation to manufacture and use of the product. Bostik is not liable for representations made by users, suppliers or retailers about the product. Bostik is not liable for any loss or damage resulting from incorrect, careless, or negligent use or storage of the product, including use of out of date product. Any liability arising from use of the product is limited to the replacement or purchase price of the product. Bostik does not exclude rights and remedies that cannot be excluded by legislation. Sale of the product by Bostik is subject to the Bostik Proprietary Limited Conditions and Terms of Sale. For more information on Bostik, products, and conditions of use and sale visit www.bostik.com