

# Sprayable Adhesive

FAST SETTING REPOSITIONABLE ADHESIVE

## TECHNICAL DATA SHEET

### SMART ADVANTAGES

- BONDS A WIDE VARIETY OF CRAFT MATERIALS
- DRIES CLEAR LEAVING AN INVISIBLE GLUE LINE
- DOES NOT WRINKLE OR WARP PAPER
- REPOSITIONABLE OR PERMANENT BONDS

### DESCRIPTION

Bostik Sprayable Adhesive is a quick, easy to use sprayable adhesive which provides a clear repositionable or permanent bond to a wide variety of craft materials making it ideal for hobbies and school projects. The adhesive is acid free and will not stain or wrinkle surfaces. It has excellent initial grab and long tack life making it ideal for solving difficult assembly and positioning problems such as bonding to a vertical surface.

### APPLICATIONS

Ideal as a clear, fast drying general purpose glue for home, school and office work, where it can be used for art and crafts, decoupage, scrap booking, archiving, photo albums, photo mounting, school projects, handicraft and decorative work, greeting cards, invitations, paper decorations, general DIY tasks where quick repairs are required. Ideal for holding stencils in place and for mounting mock ups.

### ADHESION

Exhibits good adhesion to most surfaces such as paper, board, fabric, cork, photographic paper, polyurethane foam, wood, glass, many plastics, fiberglass, metals, and painted surfaces.

### LIMITATIONS

- Will not adhere to some plastics, e.g. polyethylene, polypropylene, Teflon, plasticized PVC, etc.
- Not suitable for use on expanded polystyrene.
- Not suitable for applications needing heat resistance above 50°C.

### SAFETY INSTRUCTIONS

Bostik Sprayable Adhesive contains a flammable solvent. Always work in a ventilated area. Do not breathe in vapours. Avoid exposing product to any ignition sources. Do not smoke when working with Bostik Sprayable Adhesive. It is advisable to wear gloves in order to avoid direct contact with the skin. If product comes in to contact with skin or eyes, rinse thoroughly and immediately with water. Seek medical assistance if irritation or discomfort persists. The container is pressurised! Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn container even when empty. Keep out of reach of children! Refer to our Safety Data Sheets for further toxicological information and comprehensive handling instructions.

### SURFACE PREPARATION

Surfaces must be clean, dry, and free of loose materials, dust, dirt, oil, rust and any other contaminants. Metal surfaces should be degreased with suitable solvents e.g. acetone. Rubber should be pre-cleaned with lacquer thinners. Hard plastics should be lightly abraded with emery paper.



## HOW TO USE

1. Not to be used if ambient temperature is below 5°C or above 35°C.
2. Protect the work surface to prevent contamination caused by overspray.
3. Test product for suitability on a small area before using on new or unfamiliar applications and materials.
4. Shake can thoroughly before use.
5. Spray adhesive evenly from 15cm to 20cm away, avoiding overspray on surrounding surfaces.
6. *For pressure sensitive repositionable bonds*, apply a light coat to one surface. Allow to adhesive to dry for 1 – 3 minutes and press together.
7. *For permanent bonds*, apply a heavy coating to both surfaces. Allow to dry for 1 – 5 minutes and press together.
8. Always clean the nozzle after use by inverting the can and spraying for a few seconds.

## CLEANING

Wet adhesive can be cleaned from non-porous surfaces with White Spirits, Mineral turpentine (Turps).

## STORAGE STABILITY

Bostik Art & Craft Sprayable Adhesive has a shelf life of at least 24 months if stored in a cool (below 25°C), dry place. If the material is kept beyond the recommended shelf life, it is not necessarily unusable, but a check should be performed to observe whether the product is still workable.

## PRODUCT PACKAGING

- 250ml aerosol can

PRODUCT DATA	
Type	Synthetic solvent based rubber spray
Appearance	Clear spray
Application temperature	15°C to 30°C (Don't use below 5°C and above 35°C)
Drying time	2 – 5 minutes at room temperature
Heat Resistance	Up to 50°C

## DISCLAIMER

The above information is only offered as a guide to the use of this product. Furthermore, users should satisfy themselves that it is suitable for their needs. Since we have no control over the conditions under which it is used, we cannot accept responsibility for the problems caused by the use and/or application of this product.

Head Office: +27(0)21 555 7400  
 Beverley Close, Montague Gardens, 7441  
 PO Box 37008, Chempet, 7442  
[www.bostik.co.za](http://www.bostik.co.za)

**ASK A STICKY QUESTION...**

**[www.stickyquestions.co.za](http://www.stickyquestions.co.za)**

**0800 222 400**

