

# Invisible Tape

## Matt Transparent Tape

### TECHNICAL DATA SHEET

#### SMART ADVANTAGES

- TRANSPARENT VIRTUALLY INVISIBLE ON PAPER
- INVISIBLE WHEN PHOTOCOPYING
- MATT SURFACE THAT CAN BE WRITTEN ON WITH PEN OR PENCIL
- DURABLE METAL BLADE FOR PRECISION CUTTING

#### DESCRIPTION

Bostik Invisible Tape is a pressure-sensitive polypropylene tape that has a matt surface which is virtually invisible on paper. It is non-yellowing and can be written on with pen, pencil or marker. Ideal for photocopiers and faxes. Bostik Invisible Tape is available in two formats, an 18mm x 20m dispenser and a twin pack 12mm x 12.7m dispenser. Both dispenser types have a durable metal blade for precision cutting of the tape.

#### APPLICATIONS

Ideal home, office and school, where it can be used for gift wrapping, sealing of boxes, holding up posters, labelling of files, art and crafts, scrap booking, photo albums, handicraft, decorative work and temporary repairs.

#### ADHESION

Bostik Invisible Tape bonds to most materials like paper, card, foil, glass, metal, wood and plastics.

#### LIMITATIONS

- Not for heavy duty use.
- May damage fragile papers on removal.
- Not suitable where heat resistance is required.

#### SAFETY INSTRUCTIONS

Use dispenser with caution as it contains a sharp edge. Keep out of reach of small children! Does not contain natural rubber latex.

#### SURFACE PREPARATION

Ensure that surfaces are clean, dry and free of any dust, grease and loose materials.

#### HOW TO USE

1. Pull tape to desired length and cut with the serrated edge of the dispenser.
2. Apply to surfaces and press firmly over the entire area.

#### CLEANING

Easily removed from most surfaces. Adhesive residue can be removed with acetone from non-porous surfaces.

#### STORAGE STABILITY

The shelf life of the product is 36 months when stored at room temperature.



# TECHNICAL DATA SHEET

## PRODUCT PACKAGING

- Bostik Invisible Tape Dispenser – 1 x (18mm x 10m)
- Bostik Twin Pack Invisible Tape Dispensers – 2 x (12mm x 12.7m)

## PRODUCT CHARACTERISTICS

Appearance	White sticky tape
Film type	Biaxial orientated polypropylene
Film thickness	50 $\mu$
pH	7 – 8

## TYPICAL PERFORMANCE DATA

Temperature resistance	-10 to 60°C
Tack	>6 [GB/T4852-2002]
Tensile strength	>60 N/25mm [GB/T7753-1987]
Peel Adhesion (180°)	>3.0 N/25mm [GB/T2792-1998]
Water resistance	Good

## DISCLAIMER

The above information is only offered as a guide to the use of this product. Furthermore, users should satisfy themselves that it is suitable for their needs. Since we have no control over the conditions under which it is used, we cannot accept responsibility for the problems caused by the use and/or application of this product.

Head Office: +27(0)21 555 7400  
Beverly Close, Montague Gardens, 7441  
PO Box 37008, Chempet, 7442  
[www.bostik.co.za](http://www.bostik.co.za)

ASK A STICKY QUESTION...

[www.stickyquestions.co.za](http://www.stickyquestions.co.za)

0800 222 400

