



Soft Plastics Adhesive

A WATER RESISTANT ADHESIVE

Date: 20 July 2018

Fact Sheet No.: TDS00465

YOUR SMART ADVANTAGES

- Extra strong
- Quick drying
- Ideal for inflatables

USES

Bostik Soft Plastics Adhesive is a strong water resistant, adhesive designed for bonding most common soft plastics. It bonds rapidly to form a strong but flexible, water resistant seal.

Bostik Soft Plastics Adhesive is suitable for bonding flexible PVC, polyurethane, natural and sulfochlorinated rubbers. Typical applications include repairing inflatables, plastic raincoats, tents and waders.

PRODUCT CHARACTERISTICS

Colour	Clear
Form	Paste
Specific Gravity	0.87 approx.
Composition	Polyurethane polymers in a solvent mixture containing butanone and acetone
Product Code	30803650 20ml tubes 1 x 6 blister
Storage/Shelf Life	Store for up to 12 months from date of manufacture when stored in the original, unopened packaging under dry conditions within the temperature range of +5°C to +25°C and out of direct sunlight.

Odour	Ketonic
-------	---------

TYPICAL PERFORMANCE DATA (Approx.)

Drying Times	5 to 10 minutes
Setting Times	24 hours in good drying conditions

DIRECTIONS FOR USE

IMPORTANT: Before using Bostik Soft Plastics Adhesive refer to the relevant Health & Safety Data Sheet, available at www.bostik.co.uk.

PREPARATION

1. Ensure that surfaces to be bonded are clean and dry. For best results do not use below 15°C.
2. Lightly abrade very smooth shiny surfaces using fine sandpaper, taking care not to damage any areas that will be visible after bonding.
3. If using Bostik Soft Plastics Adhesive on rubber products, lightly roughen the surface to be repaired using a fine grade sandpaper.

APPLICATION

4. Always open and use adhesive products over a protected surface.
5. If required use a piece of the PVC patch provided.
6. Spread an even film of adhesive onto both surfaces.
7. Leave until almost dry (about 5 to 10 minutes).
8. Press both surfaces together firmly until bonded.
9. Replace cap immediately after use, to prevent the adhesive becoming unusable.
10. Maximum bond strength is developed after approximately 48 hours.

CLEANING

11. Clean greasy, waxy or oily surfaces with fresh acetone, twice to remove residues left by the first cleaning.
12. Wet or dry adhesive can be removed with acetone.
13. Always test sensitive surfaces before applying solvent cleaners.

PRECAUTIONS IN USE

Bostik Soft Plastics Adhesive is not suitable for silicone, EPDM or similar rubbers. It is not suitable for bonding polyolefin's e.g. polythene, polypropylene. For best results do not use below 15°C.

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.co.uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data Sheet for Bostik Soft Plastics Adhesive, available at www.bostik.co.uk.

BOSTIKHOTLINE

Smart help +44 (0) 1785 272625



This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company which may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability which cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use which is inappropriate or use which is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	Fax: 01785 241818	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	Fax: 01785 272867	technical.service@bostik.com
Safety Data Sheets	Tel: 01785 272625	Fax: 01785 212962	sds.box-eu@bostik.com