



Blu-Tack

THE ORIGINAL RE-USABLE ADHESIVE

DESCRIPTION

Permanently plastic, reusable multi purpose adhesive. Excellent adhesive qualities. Very Pliable. Non-toxic – safe for all the family.

CLASSIFICATIONS/STANDARDS PRODUCT AND PACKAGING

Tested in accordance to AS/NZ3 ISO B124:2003 (Safety of Toys – Part 3: Migration of certain elements)

FEATURES AND BENEFITS

- Permanently plastic and pliable
- Reusable
- Australian Made
- Available in strips for ease of use
- Non toxic – suitable for all the family

RECOMMENDED USES

Blu-Tack is recommended for use on non-porous surfaces such as vinyl coated wallpapers, painted surfaces, glass, metal etc.


Blu-Tack has a myriad of uses around the home, office, school, factory or workshop. Number of uses are endless but here are some examples:

- Hold up posters, cards, children's paintings, certificates, party decorations, maps, messages, etc.
- Holds in place telephones, mouse mats, calculators, ornaments to shelves, photos in albums, screws to screw drivers, holds model parts in position for painting or gluing, and picture frames straight.
- Safely stores pins, keys, screws and other small objects.
- Use in floral arrangements to keep flowers in place.
- Clean fluff from fabric and dirt from computers, model railway tracks or remove dust from hard to get at places.
- Use as a putty to block out breezes.

APPLICATION INSTRUCTIONS

SURFACE PREPARATION

1. Wash hands before use.
2. Ensure surfaces are clean; dry free from grease and



APPLICATION

Blu-Tack works because its pressure sensitive.

1. For non-laminated surfaces make a 'blob' by tearing off a piece, pull and stretch into a ball and apply to one surface.
2. For laminated surfaces cut off 3-5cm pieces of Blu-Tack, remove the release paper on one side, apply to one surface, then remove the other release paper.
3. Using good thumb pressure, apply to the other surface.

REMOVAL

To remove Blu-Tack, hold and twist off or roll it carefully off the surface. Any remaining shreds can be removed by rolling or dabbing a blob of Blu-Tack over the surfaces.

LIMITATIONS

- Do not use Blu-Tack on absorbent, silk screen printed or hand stencilled wallpaper nor on porous brickwork.
- Care should be taken on painted plaster as Blu-Tack's adhesive qualities may cause paint to come away from wall.

PROPERTIES	
Colour/s	Blue/Grey
Specific Gravity	Approx. 1.9
Physical Form	Putty Strips
Chemical Type	Synthetic Polymer Base
Solids Content	100%
Solubility	Insoluble in water

STORAGE & SHELF LIFE

Store away from heat, strong oxidising agents and acids. Shelf life is 5 years if stored in room/indoor conditions.

HEALTH & SAFETY

Non harmful.

Does not contain latex.

For more detailed information refer to Material Safety Data Sheet.

First Aid

Not expected to cause a problem if swallowed, but if discomfort is experienced, seek medical advice.

Precaution

The adhesive properties of Blu-Tack increase over time, so take extra care when removing after a period of months. On some surfaces after a long period of time Blu-Tack can leave a slight oily mark but this can often be removed using De-Solv-It Sticky Spots, Stain Remover or lighter fluid. Before using these products, we recommend you test on a small inconspicuous area. Not suitable to support heavy objects. 0.5g holds 105g of load.

Fire

Non-flammable.

PACKAGING

Available in 75 grams in a cardboard envelope, packed in cartons of 10

DISCLAIMER:

The information in this Technical Data Sheet is intended for the assistance of users and is of a general nature. It reflects the extent of our knowledge and experience of our products and is based on tests which we believe to be reliable. However, no guarantee of accuracy can be given due to the wide range of surfaces, environmental and field conditions and variations encountered in raw materials, manufacturing equipment and methods at the place where the work is performed. Some of these will be beyond our knowledge and control. Users are asked to make sure that the TDS in their possession is the latest issue. Likewise, we recommend users carry out their own tests to determine the suitability of the product for their particular purposes.

Any claim for a defective product must be filed within 30 days of discovery of a problem and must be submitted with written proof of purchase. Claims are not transferrable or assignable and extend only to the original purchaser/user. Bostik reserves the right to inspect and alleged failure and no responsibility will be accepted unless Bostik is given the opportunity to do so. Bostik limits its liability to the replacement of the product/s proven faulty.

BOSTIK PHILIPPINES, INC.

35/F Penthouse Raffles Corporate Center
F. Ortigas Jr. Road, Ortigas Business Center
Pasig City Philippines
Tel No: +632 7900 5633 | Fax: +632 7900 5626

BOSTIK HOTLINE

Smart help +632 7900 5656

