



Super Glue Ultra+

60% BIOBASED CYANOACRYLATE

TECHNICAL SHEET NO: TDS02266 23/07/2024

SMART PRODUCT BENEFITS

- Liquid formula, 60% biobased
- Natural smell
- Colorless
- Ultra strong
- No immediately sticky fingers
- Multi materials & multi usage
- Heat & water resistant

DESCRIPTION

Bostik Fast Glue Ultra+ is the first repair glue containing 60% natural ingredients. Ultra strong and many more advantages. Not sticking to fingers, no smell, multi materials. And all that thanks to the power of Castor oil.

For household repairs and handicrafts.

Bostik Fast Glue Ultra+ Liquid has excellent bonding properties to a very broad range of materials such as wood, rubber, metal, ceramics, glass, tiles, plastic*, leather and much more.

Bostik Fast Glue Ultra+ has excellent bonding properties to a very broad range of materials, including woods, metals, plastics and elastomers. It is flexible and has exceptional resistance to water and humidity.

*Except: polyolefins (e.g. PP 7 PE) and silicone



TECHNICAL CHARACTERISTICS

Colour	Clear
Form	Liquid glue in tube
Composition	Alkyl cyanoacrylate
Specific gravity	0.97 g/m ³ (25°C)
Viscosity	140 to 120 Brookfield, 25°C Spindle 52z, 100 rpm (mPa·s)
Glass transition temperature (T _g)	92°C
Water absorption	0,24%

APPLICATION

IMPORTANT: Before using Bostik Super Glue Ultra+ refer to the relevant Health & Safety Data Sheet, available at www.bostik.co.uk.

- The surfaces must be clean, dry and free from any dust and grease.

- Before first use, screw the nozzle onto the tube and remove the cap.
- Apply a small amount of glue to one of the surfaces you want to adhere. Do not use items like tissue or a brush to spread the adhesive.
- When you are happy with the position, press the two surfaces together and hold for 15 seconds, moving it around to cover all areas.
- Once the glue is dry, you can sand it or paint it. Gently sand the edges of the glue until the desired effect is achieved. Then, with a fine paintbrush, paint the area you wish to cover.

CLEANING

- Clean the nozzle after each use and screw the cap on tightly.

STORAGE

18 months in its sealed original packaging, stored at +20°C.

Once opened, your product will keep for several months stored vertically away from light in a cool dry place.

Protect from frost.

PRECAUTIONS IN USE

Protect the work surface before use.

Product should not be eaten or used on body parts. Do not use for objects that hold hot food/liquids or high-stress joints.

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as a sealant for chlorine or other strong oxidizing materials. For safe handling information on this product, consult the Safety Data Sheet (SDS).

For any application not covered please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.co.uk for advice.

Recommendations and suggestions are for guidance only, since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik Super Glue Ultra+, available at www.bostik.co.uk.

PACKAGING

Product codes	30628684	Bostik Super Glue Ultra+
---------------	----------	--------------------------

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company that may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability that cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use that is inappropriate or use that is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top right hand corner on the front of this document.

Sales	Tel: 0844 371 1192	customer.service@bostik.com
Technical Advice	Tel: 0844 371 1197	technical.service@bostik.com
Safety Data Sheets	Tel: 01785 272625	sds.box-eu@bostik.com

DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contain herein.

Bostik Ltd
Common Road,
Stafford, ST16 3EH, UK
Phone: +44 (0)1785 272625
www.bostik.com/uk

BOSTIK HOTLINE

Smart help +44 (0)1785 272625



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.