

This safety data sheet was created pursuant to the requirements of: Regulation (EC) No. 1907/2006 and Regulation (EC) No. 1272/2008

BOSTIK BA940 MULTIOIL BIO Supercedes Date: 16-Jan-2023 Revision date 16-Jan-2023 Revision Number 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product Name BOSTIK BA940 MULTIOIL BIO

Pure substance/mixture Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use lubricant

Uses advised against None known

1.3. Details of the supplier of the safety data sheet

Company Name

Bostik Limited Common Rd ST16 3EH Stafford UK

Tel: +44 (1785) 27 26 25 Fax: +44 (1785) 25 72 36

E-mail address SDS.box-EU@bostik.com

1.4. Emergency telephone number

United Kingdom Bostik: +44 (1785) 272650

NHS: 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Aspiration hazard	Category 1 - (H304)
Aerosols	Category 1 - (H222, H229)

2.2. Label elements

Contains Hydrocarbons, C10-C13, alkanes, isoalkanes, cyclics, <2% aromatics



Signal word Danger

United Kingdom - BE Page 1 / 13

Revision date 16-Jan-2023

Supercedes Date: 16-Jan-2023 Revision Number 1

Hazard statements

H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

EU Specific Hazard Statements

BOSTIK BA940 MULTIOIL BIO

EUH066 - Repeated exposure may cause skin dryness or cracking

Precautionary Statements - EU (§28, 1272/2008)

P102 - Keep out of reach of children

P101 - If medical advice is needed, have product container or label at hand

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

P211 - Do not spray on an open flame or other ignition source

P410 + P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

P501 - Dispose of contents/ container to an approved waste disposal plant

Additional information

This product requires tactile warnings if supplied to the general public. This product requires child resistant fastenings when supplied to the general public unless the product is placed on the market in the form of aerosols or in a container with a sealed spray attachment.

2.3. Other hazards

In use, may form flammable/explosive vapour-air mixture.

PBT & vPvB

This mixture contains no substance considered to be persistent, bioaccumulating or toxic (PBT). This mixture contains no substance considered to be very persistent nor very bioaccumulating (vPvB).

SECTION 3: Composition/information on ingredients

3.1 Substances

Not applicable

3.2 Mixtures

Chemical name	EC No (EU Index No)	CAS No	Weight-%	Classification according to Regulation (EC) No. 1272/2008 [CLP]	Specific concentration limit (SCL)	REACH registration number
Ethanol	(603-002-00- 5) 200-578-6	64-17-5	>25 - <40	Flam. Liq. 2 (H225) Eye Irrit. 2 (H319)	Eye Irrit. 2:: C>=50.0%	01-2119457610- 43-XXXX
Hydrocarbons, C10-C13, alkanes, isoalkanes, cyclics, <2% aromatics	918-481-9	RR-113412-9	10 - <20	Asp. Tox. 1 (H304) (EUH066)	-	01-2119457273- 39-XXXX
Methyl ethyl ketone	(606-002-00- 3) 201-159-0	78-93-3	1 - <2.5	Eye Irrit. 2 (H319) (EUH066) STOT SE 3 (H336) Flam. Liq. 2 (H225)	-	01-2119457290- 43-XXXX

Full text of H- and EUH-phrases: see section 16

Note: ^ indicates not classified, however, the substance is listed in section 3 as it has an OEL

United Kingdom - BE Page 2 / 13

BOSTIK BA940 MULTIOIL BIO Revision date 16-Jan-2023 Supercedes Date: 16-Jan-2023 **Revision Number** 1

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

SECTION 4: First aid measures

4.1. Description of first aid measures

General advice If medical advice is needed, have product container or label at hand.

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for Inhalation

breathing. (Call a doctor if symptoms occur).

Eye contact Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. Keep eye wide open

while rinsing. Get medical attention if irritation develops and persists.

Skin contact Wash skin with soap and water. In the case of skin irritation or allergic reactions see a

doctor.

Ingestion Do NOT induce vomiting. Call a doctor or poison control centre immediately.

ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE

DAMAGE.

Self-protection of the first aider Remove all sources of ignition. Use personal protective equipment as required. Avoid

contact with skin, eyes or clothing.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms Inhalation of high vapour concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting. Coughing and/ or wheezing. Difficulty in breathing.

4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically. Risk of serious damage to the lungs (by aspiration). Aspiration

may cause pulmonary edema and pneumonitis.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable Extinguishing Media Water spray, carbon dioxide (CO2), dry chemical, alcohol-resistant foam.

Unsuitable extinguishing media Full water jet.

5.2. Special hazards arising from the substance or mixture

Specific hazards arising from the

chemical

Risk of ignition. Keep product and empty container away from heat and sources of ignition. In the event of fire, cool tanks with water spray. Containers may explode when

heated.

Carbon monoxide. Carbon dioxide (CO2). Hazardous combustion products

5.3. Advice for firefighters

Special protective equipment and Wear self contained breathing apparatus for fire fighting if necessary.

precautions for fire-fighters

SECTION 6: Accidental release measures

United Kingdom - BE Page 3/13

Supercedes Date: 16-Jan-2023 Revision Number 1

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area).

Ensure adequate ventilation. Avoid breathing vapours or mists. Use personal protective

Revision date 16-Jan-2023

equipment as required. Avoid contact with skin, eyes or clothing.

Other information Ventilate the area. Refer to protective measures listed in Sections 7 and 8.

For emergency responders Use personal protection recommended in Section 8.

6.2. Environmental precautions

BOSTIK BA940 MULTIOIL BIO

Environmental precautions Prevent product from entering drains. Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

Methods for containment Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth,

diatomaceous earth, vermiculite) and place in container for disposal according to local /

national regulations (see Section 13).

Methods for cleaning up

Take precautionary measures against static discharges. Take up mechanically, placing in

appropriate containers for disposal.

Prevention of secondary hazards Eliminate all ignition sources if safe to do so.

6.4. Reference to other sections

Reference to other sections See section 8 for more information. See section 13 for more information.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking. Contents under pressure. Do not puncture or incinerate cans. Ensure adequate ventilation. Avoid breathing vapours or mists. Use personal protection equipment. Avoid contact with skin, eyes or clothing. Empty containers pose a potential fire and explosion

hazard. Do not cut, puncture or weld containers.

General hygiene considerations Do not eat, drink or smoke when using this product. Wash hands before breaks and after

work. Take off all contaminated clothing and wash it before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Storage Conditions Store in accordance with the particular national regulations. Protect from sunlight. Keep

away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric

motors and static electricity). Keep at a temperature not exceeding 50 °C.

Recommended storage

temperature

Keep at temperatures between 10 and 35 °C.

7.3. Specific end use(s)

Specific use(s)

lubricant.

Risk Management Methods (RMM) The information required is contained in this Safety Data Sheet.

Other information Observe technical data sheet.

SECTION 8: Exposure controls/personal protection

United Kingdom - BE Page 4 / 13

BOSTIK BA940 MULTIOIL BIO Supercedes Date: 16-Jan-2023 Revision date 16-Jan-2023 Revision Number 1

8.1. Control parameters

Exposure Limits

Chemical name	European Union	United Kingdom
Ethanol	-	TWA: 1000 ppm
64-17-5		TWA: 1920 mg/m ³
		STEL: 3000 ppm
		STEL: 5760 mg/m ³
Hydrocarbons, C10-C13, alkanes, isoalkanes, cyclics,	-	Vapour
<2% aromatics		RCP-TWA 1200 mg/m ³
RR-113412-9		184 ppm
		Total hydrocarbons (ExxonMobil)
Butane	-	TWA: 600 ppm
106-97-8		TWA: 1450 mg/m ³
		STEL: 750 ppm
		STEL: 1810 mg/m ³
Methyl ethyl ketone	TWA: 200 ppm	TWA: 200 ppm
78-93-3	TWA: 600 mg/m ³	TWA: 600 mg/m ³
	STEL: 300 ppm	STEL: 300 ppm
	STEL: 900 mg/m ³	STEL: 899 mg/m ³
		Sk*

Chemical name	European Union	Ireland	United Kingdom
Hydrocarbons, C10-C13, alkanes,	-	-	1200 mg/m ³
isoalkanes, cyclics, <2% aromatics			171ppm
RR-113412-9			8h TWA
Methyl ethyl ketone	-	70 µmol/L (urine - Butan-2-one post	70 µmol/L urine
78-93-3		shift)	

Derived No Effect Level (DNEL) No information available

Derived No Effect Level (DNEL)				
Ethanol (64-17-5)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
worker Long term Systemic health effects	Inhalation	950 mg/m³		
worker Long term Systemic health effects	Dermal	343 mg/kg bw/d		

Methyl ethyl ketone (78-93-3)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor
worker Long term Systemic health effects	Dermal	1161 mg/kg bw/d	
worker Long term Systemic health effects	Inhalation	600 mg/m³	

Derived No Effect Level (DNEL)				
Ethanol (64-17-5)				
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
Consumer Long term Systemic health effects	Inhalation	114 mg/m³		

United Kingdom - BE Page 5 / 13

BOSTIK BA940 MULTIOIL BIO
Supercedes Date: 16-Jan-2023
Revision Number 1

Consumer	Dermal	206 mg/kg bw/d	
Long term			
Systemic health effects			
Consumer	Oral	87 mg/kg bw/d	
Long term			
Systemic health effects			

Methyl ethyl ketone (78-93-3)	Methyl ethyl ketone (78-93-3)			
Туре	Exposure route	Derived No Effect Level (DNEL)	Safety factor	
Consumer Long term Systemic health effects	Dermal	412 mg/kg bw/d		
Consumer Long term Systemic health effects	Inhalation	106 mg/m³		
Consumer Local health effects Systemic health effects	Oral	31 mg/kg bw/d		

Predicted No Effect Concentration No information available. **(PNEC)**

Predicted No Effect Concentration (PNEC)			
Ethanol (64-17-5)			
Environmental compartment	Predicted No Effect Concentration (PNEC)		
Freshwater	154 mg/l		
Marine water	15.4 mg/l		
Sewage treatment plant	100 mg/l		

Methyl ethyl ketone (78-93-3)		
Environmental compartment	Predicted No Effect Concentration (PNEC)	
Freshwater	55.8 mg/l	
Marine water	55.8 mg/l	
Freshwater sediment	287.74 mg/l	
Marine sediment	287.7 mg/l	
Soil	22.5 mg/l	

8.2. Exposure controls

Engineering controls Ensure adequate ventilation, especially in confined areas. Prevent vapour buildup by

providing adequate ventilation during and after use.

Personal protective equipment

Eye/face protection None under normal use conditions. If splashes are likely to occur, wear safety glasses

with side-shields. Eye protection must conform to standard EN 166.

Hand protection Wear suitable gloves. Recommended Use:. Nitrile rubber. Glove thickness > 0.4 mm.

Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves. The breakthrough time for the mentioned glove material is in general greater than 240 min. Gloves must

conform to standard EN 374

Skin and body protection Respiratory protection

Wear appropriate personal protective clothing to prevent skin contact.

None under normal use conditions. In case of inadequate ventilation wear respiratory

protection.

Recommended filter type: Wear a respirator conforming to EN 140 with Type A/P2 filter or better. Organic gases

and vapours filter conforming to EN 14387. brown. white.

Environmental exposure controls Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

United Kingdom - BE Page 6 / 13

BOSTIK BA940 MULTIOIL BIO Revision date 16-Jan-2023 Supercedes Date: 16-Jan-2023 **Revision Number** 1

9.1. Information on basic physical and chemical properties

Physical state Liquid Appearance Aerosol Colour Colourless Odour Solvent.

Odour threshold No information available

Remarks • Method **Property** Values

No data available Melting point / freezing point None known

Not applicable, Aerosol . Not applicable, Aerosol Initial boiling point and boiling

range

Flammability No data available None known Flammability Limit in Air None known

Upper flammability or explosive No data available

Lower flammability or explosive No data available

limits

Flash point Not applicable, Aerosol . Not applicable, Aerosol

Autoignition temperature No data available None known None known

Decomposition temperature

рΗ No data available Not applicable. Insoluble in water.

pH (as aqueous solution) No data available None known Kinematic viscosity No data available None known

Dynamic viscosity No data available

Water solubility Slightly soluble. None known Solubility(ies) No data available None known Partition coefficient No data available None known Vapour pressure No data available None known Relative density 0.71 None known

Bulk Density No data available **Liquid Density** 0.71 g/cm³

No data available Relative vapour density None known

Particle characteristics

Particle Size No information available **Particle Size Distribution** No information available

9.2. Other information

0 Solid content (%)

VOC content approx 573 g/L

9.2.1. Information with regards to physical hazard classes Not applicable

9.2.2. Other safety characteristics

No information available

Sensitivity to mechanical impact

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity Not applicable.

10.2. Chemical stability

Stability Stable under normal conditions.

Explosion data

Sensitivity to mechanical Yes.

United Kingdom - BE Page 7/13

Supercedes Date: 16-Jan-2023 Revision Number 1

impact

Sensitivity to static discharge Yes.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing.

10.4. Conditions to avoid

BOSTIK BA940 MULTIOIL BIO

Conditions to avoid Heat, flames and sparks. Excessive heat.

10.5. Incompatible materials

Incompatible materials Strong acids. Strong bases. Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition

products

None under normal use conditions. Stable under recommended storage conditions.

Revision date 16-Jan-2023

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on likely routes of exposure

Product Information

Inhalation Based on available data, the classification criteria are not met.

Eye contact Based on available data, the classification criteria are not met.

Skin contact Repeated exposure may cause skin dryness or cracking.

Ingestion Potential for aspiration if swallowed. May be fatal if swallowed and enters airways.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Inhalation of high vapour concentrations may cause symptoms like headache, dizziness,

tiredness, nausea and vomiting. Coughing and/ or wheezing. Difficulty in breathing.

Acute toxicity

Numerical measures of toxicity

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Ethanol	6200 - 15000 mg/kg (Rattus)	-	=124.7 mg/L (Rattus) 4 h
	OECD 401		
Hydrocarbons, C10-C13,	DL50 >5000 mg/kg (Rattus)	DL50 >2000 mg/kg	LC50 (8h) >5000 mg/m ³ Rat -
alkanes, isoalkanes, cyclics,		(Oryctolagus cuniculus)	Vapours
<2% aromatics			
Methyl ethyl ketone	=2483 mg/kg (Rattus)	= 5000 mg/kg (Oryctolagus	=11700 ppm (Rattus) 4 h
		cuniculus)	

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritationBased on available data, the classification criteria are not met. May cause skin irritation.

United Kingdom - BE Page 8 / 13

BOSTIK BA940 MULTIOIL BIO Supercedes Date: 16-Jan-2023 Revision date 16-Jan-2023 Revision Number 1

_

Serious eye damage/eye irritation Based on available data, the classification criteria are not met.

Methyl ethyl ketone (78-93-3)

Method	Species	Exposure route	Effective dose	Exposure time	Results
OECD Test No. 405:	Rabbit	eye			irritant
Acute Eye					
Irritation/Corrosion					

Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

Methyl ethyl ketone (78-93-3)

Method	Species	Exposure route	Results
OECD Test No. 406: Skin	Guinea pig	Dermal	No sensitisation responses
Sensitisation			were observed

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT - single exposure Based on available data, the classification criteria are not met.

STOT - repeated exposureBased on available data, the classification criteria are not met.

Aspiration hazard May be fatal if swallowed and enters airways.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties No information available.

11.2.2. Other information

Other adverse effects No information available.

SECTION 12: Ecological information

12.1. Toxicity

Ecotoxicity

Chemical name	Algae/aquatic	Fish	Toxicity to	Crustacea	M-Factor	M-Factor
	plants		microorganisms			(long-term)
Ethanol	EC50 72hr 12.9	LC50: >100mg/L	EC50 = 34634	LC50: (48h,		
64-17-5	g/l (Selenastrum	(96h,	mg/L 30 min	Daphnia magna)		
	capricornutum)	Pimephales	EC50 = 35470	EC50: =12.34		

United Kingdom - BE Page 9 / 13

Revision date 16-Jan-2023

Supercedes Date: 16-Jan-2023 Revision Number 1

	NOEC 3.24 g/l (Skeletonema costatum)	promelas)	mg/L 5 min	mg/L	
Hydrocarbons, C10-C13, alkanes, isoalkanes, cyclics, <2% aromatics RR-113412-9	LEO (72h) =1000 mg/L Algae (Pseudokirchner iella subcapitata)	,,	-	LEO (48h) =1000 mg/L (Daphnia magna)	
Methyl ethyl ketone 78-93-3	EC50=1972 mg/l (Pseudokirchner iella subcapitata)	3320mg/L (96h,	EC50 = 3403 mg/L 30 min EC50 = 3426 mg/L 5 min	EC50 48 h > 308 mg/L (Daphnia magna)	

12.2. Persistence and degradability

BOSTIK BA940 MULTIOIL BIO

Persistence and degradability No information available.

Methyl ethyl ketone (78-93-3)

Method	Exposure time	Value	Results
OECD Test No. 301D: Ready	28 days	biodegradation	98 % Readily biodegradable
Biodegradability: Closed Bottle Test	-	-	
(TG 301 D)			

12.3. Bioaccumulative potential

Bioaccumulation

Component Information

Chemical name		Partition coefficient				
	Ethanol	-0.35				
	Methyl ethyl ketone	0.3				

12.4. Mobility in soil

Mobility in soil No information available.

12.5. Results of PBT and vPvB assessment

PBT and vPvB assessment

Chemical name	PBT and vPvB assessment	
Ethanol	The substance is not PBT / vPvB PBT assessment does	
	not apply	
Hydrocarbons, C10-C13, alkanes, isoalkanes, cyclics, <2%	The substance is not PBT / vPvB	
aromatics		
Methyl ethyl ketone	The substance is not PBT / vPvB	

12.6. Endocrine disrupting properties

Endocrine disrupting properties No information available.

12.7. Other adverse effects

No information available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

United Kingdom - BE Page 10 / 13

BOSTIK BA940 MULTIOIL BIO Revision date 16-Jan-2023 Supercedes Date: 16-Jan-2023 **Revision Number 1**

Waste from residues/unused Dispose of contents/container in accordance with local, regional, national, and

products international regulations as applicable.

Empty containers pose a potential fire and explosion hazard. Do not cut, puncture or Contaminated packaging

weld containers. Pressurized container: Do not pierce or burn, even after use.

European Waste Catalogue 16 05 04* gases in pressure containers (including halons) containing dangerous

substances

15 01 04 metallic packaging

Other information Waste codes should be assigned by the user based on the application for which the

product was used.

SECTION 14: Transport information

Keep from freezing. Note:

Land transport (ADR/RID)

UN1950 14.1 UN number or ID number 14.2 Proper Shipping Name Aerosols 14.3 Transport hazard class(es) Labels 2.1

14.4 Packing group Not regulated

UN1950, Aerosols, 2, (D) Description

14.5 Environmental hazards Not applicable 14.6 Special Provisions 190, 327, 344, 625

Classification code 5F **Tunnel restriction code** (D) Limited quantity (LQ) 1 L

IMDG

14.1 UN number or ID number UN1950 14.2 Proper Shipping Name Aerosols 14.3 Transport hazard class(es) 2.1

14.4 Packing group Not regulated

Description UN1950, Aerosols, 2.1, (0°C c.c.)

14.5 Marine pollutant

14.6 Special Provisions 63,190, 277, 327, 344, 381, 959

Limited Quantity (LQ) See SP277 F-D. S-U FmS-No 14.7 Maritime transport in bulk Not applicable

according to IMO instruments

Air transport (ICAO-TI / IATA-DGR)

14.1 UN number or ID number UN1950

14.2 Proper Shipping Name Aerosols, flammable

14.3 Transport hazard class(es) 2.1

14.4 Packing group Not regulated

UN1950, Aerosols, flammable, 2.1 Description

Not applicable 14.5 Environmental hazards 14.6 Special Provisions A145, A167, A802

Limited quantity (LQ) 30 kg G **ERG Code** 10L

Section 15: REGULATORY INFORMATION

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

European Union

United Kingdom - BE Page 11/13

BOSTIK BA940 MULTIOIL BIO Supercedes Date: 16-Jan-2023 Revision date 16-Jan-2023 Revision Number 1

Take note of Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work

Check whether measures in accordance with Directive 94/33/EC for the protection of young people at work must be taken.

Take note of Directive 92/85/EC on the protection of pregnant and breastfeeding women at work

Registration, Evaluation, Authorization, and Restriction of Chemicals (REACh) Regulation (EC 1907/2006)

SVHC: Substances of Very High Concern for Authorisation:

This product does not contain candidate substances of very high concern at a concentration >=0.1% (Regulation (EC) No. 1907/2006 (REACH), Article 59)

EU-REACH (1907/2006) - Annex XVII - Substances subject to Restriction

This product does not contain substances subject to restriction (Regulation (EC) No. 1907/2006 (REACH), Annex XVII).

Substance subject to authorisation per REACH Annex XIV

This product does not contain substances subject to authorisation (Regulation (EC) No. 1907/2006 (REACH), Annex XIV)

Ozone-depleting substances (ODS) regulation (EC) 1005/2009

Not applicable

Persistent Organic Pollutants

Not applicable

National regulations

15.2. Chemical safety assessment

Chemical Safety Assessments have been carried out by the Reach registrants for substances registered at >10 tpa. No Chemical Safety Assessment has been carried out for this mixture

SECTION 16: Other information

Key or legend to abbreviations and acronyms used in the safety data sheet

Full text of H-Statements referred to under section 3

EUH066 - Repeated exposure may cause skin dryness or cracking

H225 - Highly flammable liquid and vapour

H304 - May be fatal if swallowed and enters airways

H319 - Causes serious eye irritation

H336 - May cause drowsiness or dizziness

Legend

TWA TWA (time-weighted average)
STEL STEL (Short Term Exposure Limit)

Ceiling Ceiling Limit Value
* Skin designation

SVHC Substance(s) of Very High Concern

PBT Persistent, Bioaccumulative, and Toxic (PBT) Chemicals vPvB Very Persistent and very Bioaccumulative (vPvB) Chemicals

United Kingdom - BE Page 12/13

Supercedes Date: 16-Jan-2023 Revision Number 1

Revision date 16-Jan-2023

STOT RE Specific target organ toxicity - Repeated exposure STOT SE Specific target organ toxicity - Single exposure

EWC European Waste Catalogue

ADR European Agreement concerning the International Carriage of Dangerous Goods by

Road

IMDG International Maritime Dangerous Goods (IMDG)
IATA International Air Transport Association (IATA)

RID Regulations concerning the International Transport of Dangerous Goods by Rail

Key literature references and sources for data

No information available

BOSTIK BA940 MULTIOIL BIO

Prepared By Product Safety & Regulatory Affairs

Revision date 16-Jan-2023

Indication of changes

Revision note SDS sections updated: 1, 2, 3, 4, 5, 6, 7, 8, 9, 10, 11, 12, 13, 14, 15, 16.

Training Advice No information available

Further information No information available

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet

United Kingdom - BE Page 13 / 13