



BA940 Premium Multi-Use Spray

8 IN 1 MULTIFUNCTION SPRAY BIOBASED FORMULA

TECHNICAL DATASHEET

SMART ADVANTAGES

- Contains bio-based ingredients
- **8 in 1** function
- Spray from any position with the cobra head
- Easy to dose due to a uniform spray pattern
- High performances

PRODUCT DESCRIPTION

BOSTIK BA940 PREMIUM MULTI-USE SPRAY is the ultimate solution for many everyday tasks around the house, indoor and outdoor. It helps protecting, maintaining, cleaning automotive, furniture, DIY materials, electrical equipment... and many more! **BOSTIK BA940 PREMIUM MULTI-USE SPRAY** contains biobased ingredients: 30% of bioethanol and 20% of bio-based oil. It is also silicone-free.

8 FUNCTIONS

1. **LOOSENS** stuck parts
2. **PROTECTS** against corrosion and rust on bicycles, strollers, chrome parts, motorcycles, outboard motors, and tools
3. **LUBRICATES** and allows smooth movement of hinges, rollers, springs, faucets, window and door handles, and office swivel chairs
4. **MAINTAINS** materials and mechanisms
5. **SILENCES** squeaking and creaking noises
6. **CLEANS** rust, grease, dirt, residues, and more
7. **DISPLACES** moisture from hard-to-reach areas and metal surfaces
8. **RESTORES** electrical contact



FIELDS OF APPLICATION

BOSTIK BA940 PREMIUM MULTI-USE SPRAY is the ideal tool to have in the household for many uses. Used in the automotive sector, mechanical engineering, locksmith's shops, hobby areas and many more. Well compatible with many plastics, seals and paints. Check compatibility before use.

APPLICATION

Remove the transport lock. Shake can vigorously. Apply **BOSTIK BA940 PREMIUM MULTI-USE SPRAY** thinly and selectively, then allow to react. Repeat for persistent cases. Use a cloth for cleaning. Use only outdoors and in well-ventilated areas. Application temperature -5°C to +40°C, optimum between +16°C and +25°C.

TECHNICAL SPECIFICATIONS AND DATA

Color	Transparent yellow
Form	Aerosol
Density	~0,71 g/cm ³
Processing temperature	-5°C to +40°C, optimal between +16°C and +25°C
Viscosity	22 mm ² /s (40°C)
VOC content	Approximately 573 g/L
Flow point	-33°C

STORAGE

Store in original unopened packaging for 5 years in a cool, dry place and **upright position only**. Do not remove transport protection until before processing. The storage temperature should be between +5°C and +25°C. **Do not expose to direct sunlight.**

CONSUMPTION

Depending on the application.

PRODUCT PACKAGING

- **150 ml can**
- **300 ml can**

With these instructions, we want to advise you to the best of our knowledge based on our tests and experience. However, due to the large number of possible applications and the storage and processing conditions of our products, which are beyond our control, we cannot assume any guarantee for the processing result in individual cases. Carry out your own tests. Slight discoloration of sealants possible under UV radiation. Slight color variations between batches due to product technology. No guarantee is given for absolute color fidelity. Use material from the same batch for the same project. Our technical and commercial advisory service is at your disposal. The above information is only offered as a guide to the use of this product. Furthermore, users should satisfy themselves that it is suitable for their needs. Since we have no control over the conditions under which this product is used, we cannot accept responsibility for the problems caused by the use and/or application of this product.

With the publication of this data sheet, all previous editions become invalid.
Next Revision: December 2030
Technical Data Sheet

Bostik South Africa
1 Beverley Close, Montague Gardens, 7441
PO Box 37008, Chempet, 7442
diy.bostik.com/en-ZA
+27(0) 21 555 7400
marketing.za@bostik.com

ASK A STICKY QUESTION...

www.stickyquestions.co.za
0800 222 400

