



BLACK MAXIMUM STRENGTH DUCT TAPE

REPAIR TAPE

TECHNICAL SHEET 17/12/2025

SMART ADVANTAGES

- High resistance
- Immediate repair
- Premium cloth duct tape
- Indoor & outdoor uses
- Waterproof
- UV resistant
- Temperature resistance from -10°C to +75°C
- Resistance to shocks & vibrations
- Easy to cut
- Resistance in immersion
- Suitable for all materials (plastics*, glass, wood, metal, sky fabric, leather, fabrics, ceramic, tiles, cardboard...)

*Except PP and Teflon

DESCRIPTION

This black maximum strength duct tape is an ultra-resistant tape intended for heavy duty reparation. Used for jobs where extreme bonding strength, wear resistance and resistance to elements are very important.

It is also ideal for repairing and sealing cracks, combining, and sealing broken/torn pieces, or bundling objects. Due to excellent adhesion and resistance characteristics, this tape ensures long-lasting and heavy-duty repair.

Ideal for repair on all smooth and rough surfaces, this tape can be applied indoor and outdoor as it is bonding all materials (plastics*, glass, wood, metal, sky fabric, leather, fabrics, ceramic, tiles, cardboard...)



TECHNICAL CHARACTERISTICS

Color	Black
Adhesive	Hot melt
UV Resistant	Yes
Temperature resistance	From -10°C to +75°C
Water resistance	Waterproof & resistance in immersion
Easy to cut by hand	Yes
Odor	No
Chuck material	Recycled Cardboard
Tape width	50mm
Tape length	20m

COVERAGE

- Width: 50mm
- Length: 20m

APPLICATION

PREPARATION

- Upon application, the treated surface must be clean, dry, and free from dust and grease.
- The indicated level of performance will be reached after bonding period of 24h.

APPLICATION

- Avoid touching the exposed adhesive surface to keep full adhesive performance.
- Shear by hand (or cut).
- Apply to the repair area and press strongly and evenly for 30 sec to get the best adhesion.
- The tape needs to be pressed strongly and evenly to remove air bubbles and trigger the adhesive reaction.

CLEANING

If any residue remains after peeling off the tape, wipe it off with a cloth and acetone.

STORAGE

24 months duration after first use when stored in a clean and dry area between 10°C and 35°C.

PACKAGING

Product Code	TBC
UC	Black Maximum Strength Duct Tape
PCB	TBC
GENCOD	TBC



The application recommendations are defined by standards of use. They are imperative to respect them, but they don't need a previous try, especially for a first use or particular inconvenient of support, site or environment. Consult our safety data sheets for precautions to use.

DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contained herein.

With the publication of this data sheet, all previous editions become invalid.
Next Revision: December 2030
Technical Data Sheet

Bostik South Africa
1 Beverley Close, Montague Gardens, 7441
PO Box 37008, Chempet, 7442
diy.bostik.com/en-ZA
+27(0) 21 555 7400
marketing.za@bostik.com

ASK A STICKY QUESTION...

www.stickyquestions.co.za
0800 222 400



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.