



# CLEAR MAXIMUM STRENGTH DUCT TAPE

## REPAIR TAPE

TECHNICAL SHEET 17/12/2025

### SMART ADVANTAGES

- High resistance
- Immediate repair
- Transparent
- UV resistance
- Indoor & outdoor uses
- Waterproof
- Temperature resistance from -10°C to +75°C
- Resistance to shocks & vibrations
- Suitable for all materials (plastics\*, glass, wood, metal, sky fabric, leather, fabrics, ceramic, tiles, cardboard...)

\*Except PP and Teflon

### DESCRIPTION

This clear maximum strength duct tape is used for sealing of broken or punctured surfaces where transparency and resistance to element are Imperative. Due to excellent adhesion and resistance characteristics, this tape ensures long-lasting and heavy-duty repair.

Suitable for repair of glass surfaces (windows, furniture, headlights, taillights, windshields), as well as for plastic elements (greenhouse covers)

Waterproof, this tape can be applied on different substrates (plastics\*, glass, wood, metal, sky fabric, leather, fabrics, ceramic, tiles, cardboard...) indoors and outdoors.

Resists UV, humidity, frost, and temperature variations (-10°C to +75°C) without any yellowing.



### TECHNICAL CHARACTERISTICS

<b>Color</b>	Clear
<b>Adhesive</b>	Water acrylic
<b>Elongation</b>	550%
<b>UV Resistant</b>	Yes
<b>Temperature resistance</b>	From -10°C to 75°C
<b>Water resistance</b>	Waterproof & resistance in immersion
<b>Odor</b>	No
<b>Chuck material</b>	Recycled cardboard
<b>Tape width</b>	50mm
<b>Tape length</b>	20m

## COVERAGE

- Width: 50mm
- Length: 20m

## APPLICATION

### PREPARATION

- Upon application, the treated surface must be clean, dry, and free from dust and grease.
- The indicated level of performance will be reached after bonding period of 24h.

### APPLICATION

- Avoid touching the exposed adhesive surface to keep full adhesive performance.
- Cut the tape.
- Apply to the repair area and press strongly and evenly for 30 sec to get the best adhesion.
- The tape needs to be pressed strongly and evenly to remove air bubbles and trigger the adhesive reaction.

## CLEANING

If any residue remains after peeling off the tape, wipe it off with a cloth and acetone.

## STORAGE

24 months duration after first use when stored in a clean and dry area between 10°C and 35°C.

## PACKAGING

<b>Product Code</b>	TBC
<b>UC</b>	Clear maximum strength duct tape
<b>PCB</b>	TBC
<b>GENCOD</b>	TBC



The application recommendations are defined by standards of use. They are imperative to respect them, but they don't need a previous try, especially for a first use or particular inconvenient of support, site or environment. Consult our safety data sheets for precautions to use.

## DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contained herein.

## Bostik South Africa

1 Beverley Close, Montague Gardens, 7441  
PO Box 37008, Chempet, 7442  
diy.bostik.com/en-ZA  
+27(0) 21 555 7400  
marketing.za@bostik.com

## ASK A STICKY QUESTION...

[www.stickyquestions.co.za](http://www.stickyquestions.co.za)  
0800 222 400

All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.

