



MIRACLE

MOUNTING TAPE

TECHNICAL SHEET 17/12/2025

SMART ADVANTAGES

- Transparent
- Invisible behind clear materials
- Easy Cleaning
- Remove without residue
- Water Resistant
- Suitable for bathrooms
- Super Strong
- Holds up to 10kg per roll

DESCRIPTION

This double-sided, clear miracle mounting tape can be used for temporary bonding and mounting of objects and decoration in all conditions where transparent bonding is needed.

The magic double-sided tape is water resistant and easy to use for aesthetic and long-lasting mounting.

Ideal for bonding where easy removal is needed as the tape can be removed with no leftover residue. It ensures strong adhesion with plastic, metal, ceramics, glass, and wood surfaces.

This tape is dedicated for an indoor use for fixating and mounting objects to smooth and semi-smooth surfaces and ideal to fix temporary small objects (1kg each 15cm).

APPLICATIONS

- Upon application, the treated surface should be clean, dry, and free of grease, oil, moisture, dirt, and other contaminants.
- It is suggested that the adhesive tape should be bonded between 20°C and 40°C.

DIRECTIONS FOR USE

- The surfaces should also be even, without any deformities or imperfections that can negatively affect the adhesion properties.
- Cut the tape with scissors.
- Press firmly for 30 sec to press out air bubbles and trigger an optimal adhesive reaction.
- The tape needs to be pressed strongly and evenly to remove air bubbles and trigger the adhesive reaction.
- Remove the protective lid from the tape.
- Position object and press firmly for 60 sec to get immediate adhesion.



CLEANING

If any residue remains after peeling off the tape, wipe it off with a cloth and acetone.

STORAGE STABILITY

Bostik Miracle Mounting Tape Contact has a shelf life of 24 months if stored in a safe, cool (below 25°C), and dry place in its original moisture tight container. If the material is kept beyond the recommended shelf life, it is not necessarily unusable, but a check should be performed to observe whether the product is still workable. Ensure that the container is tightly sealed while in storage to prevent solvent evaporation.

PRODUCT PACKAGING

- 19mm x 1.5m roll

PRODUCT CHARACTERISTICS

Appearance	Translucent
Type	Acrylic
Odour	None
Elongation at break	800%



The application recommendations are defined by standards of use. They are imperative to respect them, but they don't need a previous try, especially for a first use or particular inconvenient of support, site or environment. Consult our safety data sheets for precautions to use.

DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contained herein.

Bostik South Africa
Beverley Close, Montague Gardens, 7441
Head Office: +27 21 555 7400
diy.bostik.com/en-ZA

BOSTIK HELPLINE

Smart help +27 800 222 400



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.