



WATERSTOP Repair Spray

INSTANT LEAK REPAIR & PROTECTION FOR SURFACES EXPOSED TO WATER & HUMIDITY

TECHNICAL SHEET NO: TDS01669 08/09/2026

SMART ADVANTAGES

- Repairs cracks and protects surfaces exposed to water and humidity
- Resist UV, heat, frost, salt and water
- No primers required

DESCRIPTION

Bostik WATERSTOP Repair Spray is a rubber spray designed for small repair and protection jobs. It repairs cracks and provides durable protection to surfaces exposed to water and humidity.

It can be applied to many materials and surfaces including metals, mineral substrates, roofing boards and wood. However, it is not suitable for use on polyethylene, polypropylene plastics and Teflon.

Bostik WATERSTOP Repair Spray is designed for hard-to-reach areas and is easy to apply thanks to its precise applicator and non-drip formula. No tools required!



TECHNICAL CHARACTERISTICS

Colour	Grey
Form	Rubber spray
Composition	Synthetic rubber
Application temperature	-5°C to +40°C
Specific gravity	0.86 - 0.92 g/cm ³
Drying time	Approx. 1-3 hours. Full cure: minimum 8 hours (depending on coating thickness, ambient temperature and humidity).

COVERAGE

- Coverage is dependant on the application.

APPLICATION

IMPORTANT: Before using Bostik Waterstop Repair Spray refer to the relevant Health & Safety Data Sheet, available at www.bostik.com/uk.

PREPARATION

- Surfaces must be sound, clean, and free from any contaminants such as dust, oil, grease or other surface contaminants. The surface should be dry and protected from rain during product curing time.
- Cover surfaces not requiring application such as windows & window frames and protect surrounding areas with plastic sheeting prior to application.
- Use only outdoors and in a well-ventilated area, when the temperature is between -5°C and +40°C. Shake the can for at least 2 minutes.

SPRAY APPLICATION

- Shake the can for at least 2 minutes.
- Apply the spray at a distance of 25-30cm from the surface. If needed, you can apply an additional layer after skin formation (10-20 minutes depending on ambient temperature and humidity).
- Can be painted after complete curing (approx. 8 hours).

CLEANING

- Remove any splashes/spray in unwanted areas immediately. Dried product is difficult to remove.

STORAGE

- Store for up to 24 months from the date of manufacture when stored in original, unopened packaging under cool, dry conditions within the temperature range of +5°C to +25°C and out of direct sunlight. Protect from frost.

PRECAUTIONS IN USE

Bostik Waterstop Repair Spray is not suitable for use on polyethylene, polypropylene plastics and Teflon.

Do not apply Bostik Waterstop Repair Spray over roof lights, glass or windows, or in areas that will be exposed to regular foot traffic. Do not place heavy objects on top of coated areas. Do not use in aquatic environments such as ponds and fish tanks, or for drinking water tanks. Not suitable for continued water immersion.

The colour indicated on pack is a guide only. Shade variations may occur between batches.

For any application not covered, please contact Technical Services on +44 (0)1785 272625 or visit www.bostik.com/uk for advice to determine suitability for use.

Recommendations and suggestions are for guidance only since conditions of use are completely beyond our control.

For health and safety instruction, first aid measures and spillage and disposal instructions, see separate Health and Safety Data sheet for Bostik Waterstop Repair Spray, available at www.bostik.com/uk.

PACKAGING

Product codes

30634883

500ML X 12

This disclaimer is issued by Bostik Limited ("the Company") and applies to the use of any products supplied by the Company ("the Products") displayed on this Technical Data Sheet ("TDS"). Please read this disclaimer carefully before using any of the Products. Using this TDS and/or the Product constitutes your acceptance of this disclaimer. Its contents shall prevail over any directions of use and any disclaimer and/or exclusion or limitation of liability of the Company that may appear on the packaging of the Products.

This disclaimer sets out the entire financial liability of the Company (including any liability for the acts or omissions of its employees, agents and sub-contractors) to any user of the Products ("Product User") in respect of any use made or resale by the Product User, of any of the Products in this TDS.

This disclaimer does not affect the Company's liability for death or personal injury arising from the Company's negligence in respect of the Products, nor its liability for fraud, or fraudulent misrepresentation, nor any other liability that cannot be excluded or limited under applicable law.

The Company's total liability however arising and whether caused by tort (including negligence and breach of statutory duty), breach of contract or otherwise, arising in connection with the use made or resale by the Product User of any of the Products in this TDS shall be limited to the price paid for the Product by the Product User.

The Company shall not be liable to the Product User for any pure economic loss, loss of profit, loss of business, depletion of goodwill or otherwise, in each case whether direct, indirect or consequential, or any claims (including in respect of personal injury insofar as not caused by the Company's negligence) for consequential compensation whatsoever (howsoever caused) which arise out of or in connection with the use made or resale by the Product User of any of the Products in this TDS.

The Company shall not be liable to the Product User in relation to any loss for any use that is inappropriate or use that is otherwise than in accordance with the relevant instructions for use of the Products in this TDS or on the Product. Product Users are advised to confirm the suitability of the Products by their own tests.

This TDS covers just one of a large range of products supplied by the Company.

Full information on these products and advice on application is freely available from our fully trained staff throughout the country. In addition, specialist technical advice is available from our Technical Services Department. This TDS supersedes all previous TDSs relating to the Products, and users of it must ensure that it is the current issue. Destroy all previous TDS, and if in any doubt, contact the Company, quoting the code number in the top left-hand corner on the front of this document.

Telephone:	01785 272625
Sales:	customer.service@bostik.com
Technical advice:	technical.service@bostik.com
Safety data sheets:	sds.box-eu@bostik.com

DISCLAIMER

Bostik offers this Technical Data Sheet ("TDS") for descriptive and informational use only. It is not a warranty, a contract or a substitute for expert or professional advice. Please also see the local product Safety Data Sheet for health and safety considerations.

The statements, technical information, data, and recommendations contained in this TDS are provided 'AS IS' and are not warranted or guaranteed in any way. They represent typical results for the products and are based on Bostik's research only. Since the conditions and methods of use of the products are beyond our control, Bostik expressly disclaims any and all liability and damages of whatever kind or nature that may arise from any use of the products, the results therefrom, or reliance on the information contained herein.

Bostik Ltd
Common Road,
Stafford, ST16 3EH, UK
Phone: +44 (0)1785 272625
www.bostik.com/uk

BOSTIK HOTLINE

Smart help +44 (0)1785 272625



All advice, recommendations, figures and safety regulations provided are based on careful investigations, as well as the current state of our experience and are without obligation. Although the documentation has been compiled with the greatest care, we do not accept any liability for inaccuracies, mistakes, typesetting or printing errors. We reserve the right to modify the respective product if we deem it necessary. Since the design, the quality of the substrate and the processing conditions are beyond our assessment, no liability can be accepted for work performed on the basis of this documentation. We therefore advise you to carry out practical tests on site yourself. Our general Terms and Conditions of Sale and Delivery apply to all our sales and deliveries.